

2K HGS CLEAR

Description

- 2K Acrylic Urethane Clear Coat
- High Gloss High Solids
- Cost effective
- 5L 26-22210985

Technical Summary

- High gloss
- Excellent through cure
- Excellent leveling and flow





2K HGS CLEAR

Working process		
Su	bstrates:	Basecoat
	retreatment / eaning:	Clean with Duxone® Wax and Grease Remover
A	oplication:	Use recommended respirators. Refer to relevant Material Safety Data Sheet (MSDS)
		2:1 with Duxone® 2K Hardener medium or Duxone® 2K Hardener slow
		Up to 10% Duxone® 2K Thinner
s		16 – 21s Ford Cup 4 / 20°C 16 – 20s DIN 4/ 20°C
		1.3 - 1.4 mm 400 – 500 kPa 2 coats = 50 - 60 μm
		1.5 - 1.7 mm 400 - 500 kPa $2 \text{ coats} = 50 - 60 \mu\text{m}$
71717		5 - 10 min / 20°C between coats 5 - 10 min / 20°C before force drying
		Air dry: 4 – 5 hours (optimum overnight) / 20°C Bake: 20 minutes / 60°C metal temp.
		10 – 15 min, short wave 15 – 20 min, medium wave





2K HGS CLEAR

TECHNICAL DATA

Raw Material: Acrylic Urethane high gloss resin Specific Gravity: 0.97 g/mL VOC: 570 g/L (RFU, no reducer added) Volume Solids: 35.3% (RFU, no reducer added) Weight Solids: 39.2% (RFU, no reducer added) Approx. 7.1 m²/L at 50 microns DFT Coverage: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent Equipment:
VOC: 570 g/L (RFU, no reducer added) Volume Solids: 35.3% (RFU, no reducer added) Weight Solids: 39.2% (RFU, no reducer added) Approx. 7.1 m²/L at 50 microns DFT Coverage: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent
Volume Solids: 35.3% (RFU, no reducer added) Weight Solids: 39.2% (RFU, no reducer added) Approx. 7.1 m²/L at 50 microns DFT Coverage: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent
Weight Solids: 39.2% (RFU, no reducer added) Approx. 7.1 m²/L at 50 microns DFT Coverage: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent
Approx. Coverage: Potlife: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent
Coverage: Potlife: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent
Potlife: 2 hours / 20°C Cleaning of Clean after use with Duxone® Gun Wash Solvent
Clean after use with Duxone® Gun Wash Solvent
8
Equipment:
Equipment.
Important • For professional use only
Remarks: • For small spot repairs and similar applications, Duxone 2K
Hardener fast may be used

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

