


Always use correct Personal Protective Equipment


62C ACCELERATOR

Description



62C Accelerator is an additive for two pack paint systems. Addition of up to 5% by volume of 62C Accelerator to 2 pack paint systems will approximately halve curing and pot life times.

Products




Product Type: Aliphatic Polyisocyanate Resin
Colour: Clear
Density: 0.870 kg/L

Properties



VOC: 871 g/L
Volume Solids: 0.05%

Directions For Use



Mixing Ratio: Add up to 5% 62C Accelerator (by volume) to the two pack paint system.

Health & Safety



For detailed information refer to Safety Data Sheet (SDS). Contains Isocyanates, avoid contact with skin and eyes.
 Avoid breathing vapour. Use protective clothing and respiratory equipment. Product is flammable.

Transport & Storage



Sizes: 250 ml, 1 lt
Dangerous Goods: 3A
UN: 1263
Hazchem: 3[Y]E
Packing Group: II
Shipment name: PAINT Related Material (flammable)
Flash point: 4°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.