

ARMOURCOTE 210

RESENE PAINTS LTD

Chemwatch: 9-70701
Version No: 1.9
Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 3

Issue Date: 11/07/2014
Print Date: 16/07/2014
Initial Date: 16/07/2014
S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	ARMOURCOTE 210
Chemical Name	Not Applicable
Synonyms	includes GREY, WAREHOUSE MERCURY GREY, RED OXIDE, FACTORY COLOURS, PMS287 BLUE
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Details of the manufacturer/importer

Registered company name	RESENE PAINTS LTD
Address	32-50 Vogel Street, Lower Hutt, Wellington New Zealand
Telephone	+64 4 5770500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	0800 737363
Other emergency telephone numbers	0800 737363

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
+800 2436 2255	+612 9186 1132	Not Available

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Goods for transport purposes.

GHS Classification ^[1]	Flammable Liquid Category 3, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Carcinogen Category 2, Reproductive Toxicity Category 1, STOT - SE (Resp. Irr.) Category 3, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1C, 6.1D (inhalation), 6.1D (oral), 6.3A, 6.4A, 6.7B, 6.8A, 6.9 (respiratory), 9.1C, 9.1D

Label elements

GHS label elements



SIGNAL WORD

DANGER

Hazard statement(s)

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H332	Harmful if inhaled
H315	Causes skin irritation
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H335	May cause respiratory irritation
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Precautionary statement(s): Prevention

P201	Obtain special instructions before use.
------	---

Precautionary statement(s): Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
-----------	--

Precautionary statement(s): Storage

P403+P235	Store in a well-ventilated place. Keep cool.
-----------	--

Precautionary statement(s): Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1330-20-7	1-10	xylene
123-86-4	1-10	n-butyl acetate
64742-95-6.	1-10	naphtha petroleum, light aromatic solvent
763-69-9	1-10	ethyl-3-ethoxypropionate
13701-59-2	1-10	barium metaborate
1314-13-2	1-10	zinc oxide
Various	10-30	alkyd resin solution

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

Eye Contact	<ul style="list-style-type: none"> ▶ Generally not applicable.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.

Ingestion

- ▶ **If swallowed do NOT induce vomiting.**
- ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- ▶ Observe the patient carefully.
- ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- ▶ Seek medical advice.
- ▶ Avoid giving milk or oils.
- ▶ Avoid giving alcohol.
- ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

for simple esters:

BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

- ▶ After ingestion of barium acid salts, severe gastro-intestinal irritation followed by muscle twitching, progressive flaccid paralysis and severe hypokalaemia and hypertension, occurs.
- ▶ Respiratory failure, renal failure and occasional cardiac dysrhythmias may result from an acute ingestion.
- ▶ Use sodium sulfate as a cathartic. Add 5-10 gm of sodium sulfate to lavage solution or as fluid supplement to Ipecac syrup (the sulfate salt is not absorbed)
- ▶ Monitor cardiac rhythm and serum potassium closely to establish the trend over the first 24 hours. Large doses of potassium may be needed to correct the hypokalaemia.
- ▶ Administer generous amounts of fluid replacement but monitor the urine and serum for evidence of renal failure. [Ellenhorn and Barceloux: Medical Toxicology]

For acute or short term repeated exposures to xylene:

- ▶ Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- ▶ Pulmonary absorption is rapid with about 60-65% retained at rest.
- ▶ Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 < 50 mm Hg or pCO2 > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
-------------	-------	---------------	----------

Methylhippu-ric acids in urine	1.5 gm/gm creatinine	End of shift	
	2 mg/min	Last 4 hrs of shift	

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.

Fire/Explosion Hazard

- ▶ Liquid and vapour are flammable.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

- ▶ Clean up all spills immediately.

Major Spills

- ▶ Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ▶ Containers, even those that have been emptied, may contain explosive vapours.

Other information

- ▶ Store in original containers in approved flammable liquid storage area.

Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Packing as supplied by manufacturer.

Storage incompatibility

n-Butyl acetate:

- ▶ reacts with water on standing to form acetic acid and n-butyl alcohol
- ▶ reacts violently with strong oxidisers and potassium tert-butoxide
- ▶ is incompatible with caustics, strong acids and nitrates
- ▶ dissolves rubber, many plastics, resins and some coatings

Xylenes:

- ▶ may ignite or explode in contact with strong oxidisers, 1,3-dichloro-5,5-dimethylhydantoin, uranium fluoride
- ▶ attack some plastics, rubber and coatings
- ▶ may generate electrostatic charges on flow or agitation due to low conductivity.

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	xylene	Xylene (o-, m-, p-isomers)	217 mg/m ³ / 50 ppm	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	n-butyl acetate	n-Butyl acetate	713 mg/m ³ / 150 ppm	950 mg/m ³ / 200 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	barium metaborate	Barium, soluble compounds, as Ba	0.5 mg/m ³	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide Dust / Zinc oxide fume	10 mg/m ³ / 5 mg/m ³	10 mg/m ³	Not Available	The value for inhalable dust containing no asbestos and less than 1% free silica.


EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
xylene	100 ppm	130 ppm	920 ppm	2500 ppm

n-butyl acetate	5 ppm	5 ppm	200 ppm	3000 ppm
naphtha petroleum, light aromatic solvent	500 ppm	750 ppm	750 ppm	750 ppm
ethyl-3-ethoxypropionate	20 ppm	60 ppm	400 ppm	500 ppm
barium metaborate	10 ppm	30 ppm	200 ppm	500 ppm
zinc oxide	15 ppm	15 ppm	15 ppm	500 ppm

Ingredient	Original IDLH	Revised IDLH
xylene	1,000 ppm	900 ppm
n-butyl acetate	10,000 ppm	1,700 [LEL] ppm
naphtha petroleum, light aromatic solvent	Not Available	Not Available
ethyl-3-ethoxypropionate	Not Available	Not Available
barium metaborate	1,100 mg/m3	50 mg/m3
zinc oxide	2,500 mg/m3	500 mg/m3
alkyd resin solution	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC.
Body protection	See Other protection below
Other protection	▶ Overalls.
Thermal hazards	Not Available

Recommended material(s)

Respiratory protection

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

ARMOURCOTE 210

Material	CPI
PE/EVAL/PE	A
PVA	A
TEFLON	A
VITON	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Manufactured	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	428
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available

Initial boiling point and boiling range (°C)	143	Molecular weight (g/mol)	Not Available
Flash point (°C)	36	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	8.5	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	1.2	Volatile Component (%vol)	25
Vapour pressure (kPa)	1.0	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	4.2	VOC g/L	380

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period.
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

ARMOURCOTE 210	TOXICITY	IRRITATION
	Not Available	Not Available
xylene	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 5000 ppm/4h	Eye (human): 200 ppm irritant
	Intraperitoneal (Mouse) LD50: 1548 mg/kg	Eye (rabbit): 5 mg/24h SEVERE
	Intraperitoneal (Rat) LD50: 2459 mg/kg	Eye (rabbit): 87 mg mild
	Oral (Mouse) LD50: 2119 mg/kg	Skin (rabbit):500 mg/24h moderate
	Oral (rat) LD50: 4300 mg/kg	
	Subcutaneous (Rat) LD50: 1700 mg/kg	
	Not Available	Not Available
n-butyl acetate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 3200 mg/kg*	* [PPG]
	Inhalation (rat) LC50: 2000 ppm/4H	Eye (human): 300 mg
	Inhalation (Rat) LC50: 390 ppm/4h	Eye (rabbit): 20 mg (open)-SEVERE
	Intraperitoneal (Mouse) LD50: 1230 mg/kg	Eye (rabbit): 20 mg/24h - moderate
	Oral (Guinea pig) LD50: 4700 mg/kg	Skin (rabbit): 500 mg/24h-moderate
	Oral (Rabbit) LD50: 3200 mg/kg	
	Oral (Rat) LD50: 10768 mg/kg	
Oral (rat) LD50: 13100 mg/kg		
Not Available	Not Available	

naphtha petroleum, light aromatic solvent	TOXICITY	IRRITATION
	Inhalation (rat) LC50: >3670 ppm/8 h *	Nil reported
	Oral (rat) LD50: >5000 mg/kg *	
	Not Available	Not Available
ethyl-3-ethoxypropionate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 10000 mg/kg	Eye (rabbit): 500mg/24h - mild
	Dermal (rabbit) LD50: 4076 mg/kg	Skin (rabbit): 10 mg/24h open mild
	Inhalation (rat) LC50: 1250 ppm/4h	
	Oral (rat) LD50: 5000 mg/kg	
	Oral (rat) LD50: 5140 mg/kg	
	Not Available	Not Available
barium metaborate	TOXICITY	IRRITATION
	Dermal (rat) LD50: >2000 mg/kg	[CCINFO - BU]
	Inhalation (rat) LC50: 21.7 mg/Litre	
	Not Available	Not Available
zinc oxide	TOXICITY	IRRITATION
	Oral (mouse) LD50: 7950 mg/kg	Eye (rabbit) : 500 mg/24 h - mild
	Oral (Rat) LD50: >8437 mg/kg	Skin (rabbit) : 500 mg/24 h - mild
	Not Available	Not Available
alkyd resin solution	TOXICITY	IRRITATION
	Not Available	Not Available

XYLENE	Reproductive effector in rats
NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	For trimethylbenzenes: Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure. Inhalation (rat) TCLo: 1320 ppm/6h/90D-I * [Devoe]
ETHYL-3-ETHOXYPROPIONATE	* Union Carbide ** Endura Manufacturing
BARIUM METABORATE	Oral (rat) LD50: 850mg/kg Eye (human): Irritant
ALKYD RESIN SOLUTION	"alkyd resin" describes a generic insoluble polymer which has no residual hazardous reactants and is not absorbed in the gastro-intestinal tract.
ARMOURCOTE 210, BARIUM METABORATE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.
XYLENE, N-BUTYL ACETATE	The material may produce severe irritation to the eye causing pronounced inflammation.
ETHYL-3-ETHOXYPROPIONATE, ZINC OXIDE	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	⊖	STOT - Repeated Exposure	⊖
Mutagenicity	⊖	Aspiration Hazard	⊖

Legend: ✓ – Data required to make classification available
 – Data available but does not fill the criteria for classification
 ⊖ – Data Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic organisms.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
Not Available	Not Available

Mobility in soil

Ingredient	Mobility
Not Available	Not Available


SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	
	▶ Containers may still present a chemical hazard/ danger when empty.
	Insure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	+3Y

Land transport (UN)

UN number	1263
Packing group	III
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Environmental hazard	No relevant data
Transport hazard class(es)	Class 3 Subrisk Not Applicable
Special precautions for user	Special provisions 163;223;367 Limited quantity 5 L

Air transport (ICAO-IATA / DGR)

UN number	1263
Packing group	III
UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class 3 ICAO / IATA Subrisk Not Applicable ERG Code 3L
Special precautions for user	Special provisions A3A72 Cargo Only Packing Instructions 366

Cargo Only Maximum Qty / Pack	220 L
Passenger and Cargo Packing Instructions	355
Passenger and Cargo Maximum Qty / Pack	60 L
Passenger and Cargo Limited Quantity Packing Instructions	Y344
Passenger and Cargo Limited Maximum Qty / Pack	10 L

Sea transport (IMDG-Code / GGVSee)

UN number	1263
Packing group	III
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Environmental hazard	No relevant data
Transport hazard class(es)	IMDG Class : 3 IMDG Subrisk : Not Applicable
Special precautions for user	EMS Number : F-E , S-E Special provisions : 163 223 955 Limited Quantities : 5 L

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	xylene	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	n-butyl acetate	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethyl-3-ethoxypropionate	Y

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002669	Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006

xylene(1330-20-7) is found on the following regulatory lists

"International Council of Chemical Associations (ICCA) - High Production Volume List", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data", "New Zealand Inventory of Chemicals (NZIoC)", "OSPAR List of Chemicals for Priority Action", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "FisherTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "New Zealand Workplace Exposure Standards (WES)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "UNECE - Kiev Protocol on Pollutant Release and Transfer Registers - Annex II", "OECD Existing Chemicals Database", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "International Air Transport Association (IATA) Dangerous Goods Regulations", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Dangerous Goods", "International Fragrance Association (IFRA) Survey: Transparency List", "IMO IBC Code Chapter 17: Summary of minimum requirements", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Chemicals (single components)"

n-butyl acetate(123-86-4) is found on the following regulatory lists

"International Council of Chemical Associations (ICCA) - High Production Volume List", "IOFI Global Reference List of Chemically Defined Substances", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data", "New Zealand Inventory of Chemicals (NZIoC)", "FisherTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Joint FAO/WHO Expert Committee on Food Additives (JECFA) - Specifications for Flavours", "OSPAR National List of Candidates for Substitution - Norway", "New Zealand Workplace Exposure Standards (WES)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "OECD Existing Chemicals Database", "Sigma-AldrichTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "International Air Transport Association (IATA) Dangerous Goods Regulations", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Dangerous Goods", "International Fragrance Association (IFRA) Survey: Transparency List", "IMO IBC Code Chapter 17: Summary of minimum requirements", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Chemicals (single components)", "Acros Transport Information"

<p>naphtha petroleum, light aromatic solvent(64742-95-6) is found on the following regulatory lists</p>	<p>"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "New Zealand Inventory of Chemicals (NZIoC)", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "New Zealand Workplace Exposure Standards (WES)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "New Zealand Cosmetic Products Group Standard - Schedule 4: Components Cosmetic Products Must Not Contain - Table 1", "International Chemical Secretariat (ChemSec) SIN List ("Substitute It Now!)", "International Society of Automotive Engineers (SAE) Declarable Substances Chemical List - ARP9536", "OECD Existing Chemicals Database", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities", "International Air Transport Association (IATA) Dangerous Goods Regulations", "IMO IBC Code Chapter 17: Summary of minimum requirements"</p>
<p>ethyl-3-ethoxypropionate(763-69-9) is found on the following regulatory lists</p>	<p>"International Council of Chemical Associations (ICCA) - High Production Volume List", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data", "New Zealand Inventory of Chemicals (NZIoC)", "FisherTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals", "International Air Transport Association (IATA) Dangerous Goods Regulations", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Dangerous Goods", "IMO IBC Code Chapter 17: Summary of minimum requirements"</p>
<p>barium metaborate(13701-59-2) is found on the following regulatory lists</p>	<p>"International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data", "New Zealand Inventory of Chemicals (NZIoC)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "New Zealand Workplace Exposure Standards (WES)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals", "International Air Transport Association (IATA) Dangerous Goods Regulations", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Chemicals (single components)"</p>
<p>zinc oxide(1314-13-2) is found on the following regulatory lists</p>	<p>"International Maritime Dangerous Goods Requirements (IMDG Code)", "New Zealand Cosmetic Products Group Standard - Schedule 8: UV Filters Cosmetic Products May Contain With Restrictions - Table 2: Additional List of Permitted UV Filters which Cosmetic Products May contain in New Zealand", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data", "New Zealand Inventory of Chemicals (NZIoC)", "FisherTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "New Zealand Workplace Exposure Standards (WES)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "UNECE - Kiev Protocol on Pollutant Release and Transfer Registers - Annex II", "OECD Existing Chemicals Database", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Timber Preservatives, Antisapstains and Antifouling Paints", "Sigma-AldrichTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals", "International Air Transport Association (IATA) Dangerous Goods Regulations", "New Zealand Cosmetic Products Group Standard - Schedule 6 Colouring Agents Cosmetic Products May Contain With Restrictions- Table 1: List fo Colouring Agents Allowed for use in Cosmetic Products", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Veterinary Medicines", "International Fragrance Association (IFRA) Survey: Transparency List", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Chemicals (single components)", "New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits"</p>
<p>alkyd resin solution(Various) is found on the following regulatory lists</p>	<p>"International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities", "International Air Transport Association (IATA) Dangerous Goods Regulations"</p>

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
3.1C	500 L in containers greater than 5 L 1500 L in containers up to and including 5 L	250 L 250 L

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.