

RESENE ARMOURCOTE 220 BASE GREY

Resene Paints Ltd

Version No: 1.2
Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 3

Issue Date: 25/02/2015
Print Date: 25/02/2015
Initial Date: 25/02/2015
S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE ARMOURCOTE 220 BASE GREY
Synonyms	Not Available
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	7903
--------------------------	------

Details of the manufacturer/importer

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington 5011 Naenae New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)
Emergency telephone numbers	0800 764766
Other emergency telephone numbers	Not Available

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
+800 2436 2255	+612 9186 1132	Not Available

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Goods for transport purposes.

GHS Classification [1]	Acute Aquatic Hazard Category 2, Carcinogen Category 2, Chronic Aquatic Hazard Category 2, Eye Irritation Category 2A, Flammable Liquid Category 2, Reproductive Toxicity Category 2, Skin Corrosion/Irritation Category 2, Skin Sensitizer Category 1, STOT - RE Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1B, 9.1B, 6.5B (contact), 6.7B, 6.4A, 6.9B, 6.3A, 6.8B

Label elements

GHS label elements	
--------------------	---

SIGNAL WORD **DANGER**

Hazard statement(s)

Continued...

RESENE ARMOURCOTE 220 BASE GREY

H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
------	---

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
-----------	--

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
-----------	--

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
71-36-3	5-10	n-butanol
1330-20-7	10-20	xylene
25036-25-3	10-20	bisphenol A/ bisphenol A diglycidyl ether polymer
100-41-4	2-4	ethylbenzene
107-98-2	2-4	propylene glycol monomethyl ether - mixture of isomers
108-88-3	2-4	toluene

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.
Ingestion	<ul style="list-style-type: none"> ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice. ▶ Avoid giving milk or oils. ▶ Avoid giving alcohol.

Indication of any immediate medical attention and special treatment needed

for phosphate salts intoxication:

- ▶ All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Continued...

RESENE ARMOURCOTE 220 BASE GREY

- ▶ Ingestion of large quantities of phosphate salts (over 1.0 grams for an adult) may cause an osmotic catharsis resulting in diarrhoea and probable abdominal cramps. Larger doses such as 4-8 grams will almost certainly cause these effects in everyone. In healthy individuals most of the ingested salt will be excreted in the faeces with the diarrhoea and, thus, not cause any systemic toxicity. Doses greater than 10 grams hypothetically may cause systemic toxicity.
- ▶ Treatment should take into consideration both anionic and cation portion of the molecule.
- ▶ All phosphate salts, except calcium salts, have a hypothetical risk of hypocalcaemia, so calcium levels should be monitored.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- ▶ Gastric lavage with copious amounts of water.
- ▶ It may be beneficial to instill 60 ml of mineral oil into the stomach.
- ▶ Oxygen and artificial respiration as needed.
- ▶ Electrolyte balance: it may be useful to start 500 ml M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ▶ To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- ▶ Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5]

BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Anticipate and treat, where necessary, for seizures.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Acidosis may respond to hyperventilation and bicarbonate therapy.
- ▶ Haemodialysis might be considered in patients with severe intoxication.
- ▶ Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

For acute or short term repeated exposures to xylene:

- ▶ Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- ▶ Pulmonary absorption is rapid with about 60-65% retained at rest.
- ▶ Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ < 50 mm Hg or pCO₂ > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Methylhippu-ric acids in urine	1.5 gm/gm creatinine 2 mg/min	End of shift Last 4 hrs of shift	

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Alcohol stable foam.

Special hazards arising from the substrate or mixture

- | Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|----------------------|--|
|----------------------|--|

Advice for firefighters

- | Fire Fighting | ▶ Alert Fire Brigade and tell them location and nature of hazard. |
|---------------|---|
|---------------|---|

RESENE ARMOURCOTE 220 BASE GREY

Fire/Explosion Hazard	▶ Liquid and vapour are highly flammable.
------------------------------	---

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Minor Spills	▶ Remove all ignition sources.
Major Spills	▶ Clear area of personnel and move upwind.

	Personal Protective Equipment advice is contained in Section 8 of the MSDS.
--	---

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling**

Safe handling	▶ Containers, even those that have been emptied, may contain explosive vapours.
Other information	▶ Store in original containers in approved flame-proof area.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packing as supplied by manufacturer.
Storage incompatibility	<p>Xylenes:</p> <ul style="list-style-type: none"> ▶ may ignite or explode in contact with strong oxidisers, 1,3-dichloro-5,5-dimethylhydantoin, uranium fluoride ▶ attack some plastics, rubber and coatings ▶ may generate electrostatic charges on flow or agitation due to low conductivity.

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	n-butanol	n-Butyl alcohol	Not Available	Not Available	150 mg/m ³ / 50 ppm	Skin absorption
New Zealand Workplace Exposure Standards (WES)	n-butanol	Methyl ethyl ketone	445 mg/m ³ / 150 ppm	890 mg/m ³ / 300 ppm	Not Available	Exposure can also be estimated by biological monitoring.
New Zealand Workplace Exposure Standards (WES)	xylene	Xylene (o-, m-, p-isomers)	217 mg/m ³ / 50 ppm	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	ethylbenzene	Ethyl benzene	434 mg/m ³ / 100 ppm	543 mg/m ³ / 125 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	propylene glycol monomethyl ether - mixture of isomers	Propylene glycol monomethyl ether	369 mg/m ³ / 100 ppm	553 mg/m ³ / 150 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	toluene	Toluene	188 mg/m ³ / 50 ppm	Not Available	Not Available	Skin absorption

EMERGENCY LIMITS


Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
n-butanol	Butyl alcohol, n-; (n-Butanol)	20 ppm	50 ppm	8000 ppm
n-butanol	Butanone, 2-; (Methyl ethyl ketone; MEK)	Not Available	Not Available	Not Available
xylene	Xylenes	Not Available	Not Available	Not Available
bisphenol A/ bisphenol A diglycidyl ether polymer	Epoxy resin; (Bisphenol A-Bisphenol A diglycidyl ether polymer)	6 mg/m ³	66 mg/m ³	400 mg/m ³
ethylbenzene	Ethyl benzene	Not Available	Not Available	Not Available
propylene glycol monomethyl ether - mixture of isomers	Propylene glycol monomethyl ether; (Ucar Triol HG-170)	150 ppm	150 ppm	470 ppm
toluene	Toluene	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
n-butanol	8,000 ppm / 3,000 ppm	1,400 [LEL] ppm / 3,000 [Unch] ppm
xylene	1,000 ppm	900 ppm
bisphenol A/ bisphenol A diglycidyl ether polymer	Not Available	Not Available
ethylbenzene	2,000 ppm	800 [LEL] ppm
propylene glycol monomethyl ether - mixture of isomers	Not Available	Not Available
toluene	2,000 ppm	500 ppm

Continued...

RESENE ARMOURCOTE 220 BASE GREY

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	NOTE: ▶ The material may produce skin sensitisation in predisposed individuals.
Body protection	See Other protection below
Other protection	▶ Overalls.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

RESENE ARMOURCOTE 220 BASE GREY

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
CPE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/CHLOROBUTYL	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type BAX Filter of sufficient capacity.

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	BAX-AUS / Class 1	-	BAX-PAPR-AUS / Class 1
up to 25 x ES	Air-line*	BAX-2	BAX-PAPR-2
up to 50 x ES	-	BAX-3	-
50+ x ES	-	Air-line**	-

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Note that all of the monopropylene glycol ethers may exist in two isomeric forms, alpha or beta. Grey liquid with strong solvent odour		
Physical state	Liquid	Relative density (Water = 1)	1.464
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Continued...

RESENE ARMOURCOTE 220 BASE GREY

Odour threshold	Not Available	Auto-ignition temperature (°C)	470
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	120	Molecular weight (g/mol)	Not Available
Flash point (°C)	17	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.0	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.3	Volatile Component (%vol)	44
Vapour pressure (kPa)	2.9	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution	Not Available
Vapour density (Air = 1)	33	VOC g/L	380

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
Ingestion	The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models).
Skin Contact	This material can cause inflammation of the skin on contact in some persons.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

RESENE ARMOURCOTE 220 BASE GREY	TOXICITY	IRRITATION
	Not Available	Not Available
n-butanol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >8100 mg/kg ^[1]	Eye (human): 50 ppm - irritant
	Inhalation (rat) LC50: 23.5 mg/L/8H ^[2]	Eye (rabbit): 1.6 mg-SEVERE
	Inhalation (rat) LC50: 50.1 mg/L/8 hr ^[2]	Eye (rabbit): 24 mg/24h-SEVERE
	Oral (rat) LD50: 3474.9 mg/kg ^[1]	Skin (rabbit): 405 mg/24h-moderate
xylene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1700 mg/kg ^[2]	Eye (human): 200 ppm irritant
	Inhalation (rat) LC50: 5000 ppm/4h ^[2]	Eye (rabbit): 5 mg/24h SEVERE
	Oral (rat) LD50: 4300 mg/kg ^[2]	Eye (rabbit): 87 mg mild
		Skin (rabbit):500 mg/24h moderate
bisphenol A/ bisphenol A diglycidyl ether polymer	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[2]	Not Available
	Oral (rat) LD50: >2000 mg/kg ^[2]	
ethylbenzene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: ca.15432.6 mg/kg ^[1]	Eye (rabbit): 500 mg - SEVERE
	Inhalation (mouse) LC50: 35.5 mg/L/2H ^[2]	Skin (rabbit): 15 mg/24h mild
	Inhalation (rat) LC50: 55 mg/L/2H ^[2]	

RESENE ARMOURCOTE 220 BASE GREY

	Oral (rat) LD50: 3500 mg/kg ^[2]	
propylene glycol monomethyl ether - mixture of isomers	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) 230 mg mild
	Inhalation (rat) LC50: 10000 ppm/5 h.d ^[2]	Eye (rabbit) 500 mg/24 h.
	Oral (rat) LD50: 5207.2 mg/kg ^[1]	Skin (rabbit) 500 mg open - mild
toluene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 12124 mg/kg ^[2]	Eye (rabbit): 2mg/24h - SEVERE
	Inhalation (rat) LC50: >26700 ppm/1hd ^[2]	Eye (rabbit):0.87 mg - mild
	Inhalation (rat) LC50: 49 mg/L/4H ^[2]	Eye (rabbit):100 mg/30sec - mild
	Oral (rat) LD50: 636 mg/kg ^[2]	Skin (rabbit):20 mg/24h-moderate
		Skin (rabbit):500 mg - moderate
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's msds Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

N-BUTANOL	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.
XYLENE	Reproductive effector in rats
BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER	*Hexion MSDS Epikote 1001
ETHYLBENZENE	Liver changes, uterual tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded.
PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS	The material may be irritating to the eye, with prolonged contact causing inflammation. NOTE: Exposure of pregnant rats and rabbits to the substance did not give rise to teratogenic effects at concentrations up to 3000 ppm.
TOLUENE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
RESENE ARMOURCOTE 220 BASE GREY, BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER	The following information refers to contact allergens as a group and may not be specific to this product.
XYLENE, ETHYLBENZENE	The material may produce severe irritation to the eye causing pronounced inflammation.

Acute Toxicity	☹	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	☹
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	☹	Aspiration Hazard	☹

Legend: ✓ – Data required to make classification available
 ✗ – Data available but does not fill the criteria for classification
 ☹ – Data Not Available to make classification

CMR STATUS

REPROTOXIN	n-butanol	ILO Chemicals in the electronics industry that have toxic effects on reproduction	
	xylene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	
	toluene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	
SKIN	n-butanol	New Zealand Workplace Exposure Standards (WES) - Skin	Skin absorption
	toluene	New Zealand Workplace Exposure Standards (WES) - Skin	Skin absorption

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

RESENE ARMOURCOTE 220 BASE GREY

Ingredient	Persistence: Water/Soil	Persistence: Air
n-butanol	LOW (Half-life = 54 days)	LOW (Half-life = 26.75 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
propylene glycol monomethyl ether - mixture of isomers	LOW (Half-life = 56 days)	LOW (Half-life = 1.7 days)
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
n-butanol	LOW (BCF = 64)
xylene	MEDIUM (BCF = 740)
ethylbenzene	LOW (BCF = 79.43)
propylene glycol monomethyl ether - mixture of isomers	LOW (BCF = 2)
toluene	LOW (BCF = 90)

Mobility in soil

Ingredient	Mobility
n-butanol	MEDIUM (KOC = 2.443)
ethylbenzene	LOW (KOC = 517.8)
propylene glycol monomethyl ether - mixture of isomers	HIGH (KOC = 1)
toluene	LOW (KOC = 268)



SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> Containers may still present a chemical hazard/ danger when empty.
	Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	
HAZCHEM	•3YE

Land transport (UN)

UN number	1263				
Packing group	II				
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)				
Environmental hazard	No relevant data				
Transport hazard class(es)	<table border="1"> <tr> <td>Class</td> <td>3</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table>	Class	3	Subrisk	Not Applicable
Class	3				
Subrisk	Not Applicable				
Special precautions for user	<table border="1"> <tr> <td>Special provisions</td> <td>163;367</td> </tr> <tr> <td>Limited quantity</td> <td>5 L</td> </tr> </table>	Special provisions	163;367	Limited quantity	5 L
Special provisions	163;367				
Limited quantity	5 L				

Air transport (ICAO-IATA / DGR)

UN number	1263
Packing group	II

RESENE ARMOURCOTE 220 BASE GREY

UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)	
Environmental hazard	No relevant data	
Transport hazard class(es)	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
Special precautions for user	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	364
	Cargo Only Maximum Qty / Pack	60 L
	Passenger and Cargo Packing Instructions	353
	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

Sea transport (IMDG-Code / GGVSee)

UN number	1263	
Packing group	II	
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
Environmental hazard	Not Applicable	
Transport hazard class(es)	IMDG Class	3
	IMDG Subrisk	Not Applicable
Special precautions for user	EMS Number	F-E , S-E
	Special provisions	163
	Limited Quantities	5 L

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	n-butanol	Z
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	xylene	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethylbenzene	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	propylene glycol monomethyl ether - mixture of isomers	Z
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	toluene	Y

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002669	Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006

n-butanol(71-36-3) is found on the following regulatory lists	"New Zealand Inventory of Chemicals (NZIoC)", "New Zealand Workplace Exposure Standards (WES)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals"
xylene(1330-20-7) is found on the following regulatory lists	"New Zealand Inventory of Chemicals (NZIoC)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "New Zealand Workplace Exposure Standards (WES)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals"
bisphenol A/ bisphenol A diglycidyl ether polymer(25036-25-3) is found on the following regulatory lists	"New Zealand Inventory of Chemicals (NZIoC)"

RESENE ARMOURCOTE 220 BASE GREY

ethylbenzene(100-41-4) is found on the following regulatory lists	"New Zealand Inventory of Chemicals (NZIoC)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "New Zealand Workplace Exposure Standards (WES)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals"
propylene glycol monomethyl ether - mixture of isomers(107-98-2) is found on the following regulatory lists	"New Zealand Inventory of Chemicals (NZIoC)", "New Zealand Workplace Exposure Standards (WES)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals"
toluene(108-88-3) is found on the following regulatory lists	"New Zealand Inventory of Chemicals (NZIoC)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "New Zealand Workplace Exposure Standards (WES)", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals"

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
3.1B	100 L in containers greater than 5 L 250 L in containers up to and including 5 L	50 L 50 L

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
3.1B	250 L (when in containers greater than 5 L) 500 L (when in containers up to and including 5 L)

SECTION 16 OTHER INFORMATION**Other information****Ingredients with multiple cas numbers**

Name	CAS No
propylene glycol monomethyl ether - mixture of isomers	107-98-2, 1320-67-8., 28677-93-2

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.