ARMOURZINC 110 Version Number: 4

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: ARMOURZINC 110

Other Names:

Recommended Use: Formerly known as RUST-ANODE, TRANSCOTE ZINC RICH

Company Name: Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND

P O Box 38242, Wellington Mail Centre

Phone: (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214

P O Box 785, Ashmore City, Queensland 4214

AUSTRALIA

Phone 1800 738 38 Emergency Telephone:

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

Australian Poisons Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Regulated under NZS5433 for land transportation

Risk Phrases Not assigned Safety Phrases Not assigned

Substance Classification 3.1C 6.3A 6.4A 6.5B 6.8A 6.9B 9.1A

Hazard Statements Flammable liquid and vapour

Causes skin irritation Causes eye irritation

May cause an allergic skin reaction May damage fertility or the unborn child.

May cause respiratory irritation
May cause drowsiness or dizziness

Very toxic to aquatic life with long lasting effects

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENT

Ingredients	%	CAS No	TWA	
Zinc	>60	7440-66-6	0.1 mg/m ³ as I	NZ OSH (WES) 2002
Dimethylbenzene	1-10	1330-20-7	217 mg/m ³	NZ OSH (WES) 2002
Aromatic Hydrocarbon	1-10	64742-95-6	not known	
Proprietary ingredients	1-10	various	None Establish	

SECTION 4. FIRST AID MEASURES

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel

unwell.

Skin Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and

plenty of soap. If skin irritation occurs get medical advice/attention.

Inhaled Remove to fresh air and keep at rest in a position comfortable for breathing.

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified

Advice to Doctor Treat Symptomatically

SECTION 5. FIRE FIGHTING MEASURES

ARMOURZINC 110 Page 1 of 4 Resene Paints Limited

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

484℃ 7.4% 0.9% **Hazchem Code** Flash Point

32℃ 3[Y]

ACCIDENTAL RELEASE MEASURES SECTION 6.

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities

Storage Temperatures Max 40°C Min 0ºC

Incompatibilities

EXPOSURE CONTROLS/PERSONAL PROTECTION SECTION 8.

National exposure

No exposure standards has been established for this product

standards for mixture

Breathing Zone ppm Breathing Zone mg/m³ Component

Personal Protection

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using

any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet

recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

Respirator Type A organic filter of sufficient capacity

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Grey liquid

Vapour Pressure Vapour Density Hq **Boiling Point** Melt Freeze Odour Solubility

Volatile by Weight 0℃ 142℃ Hydrocarbon n/a 0.8 kPa 3.8 Insoluble 15

STABILITY AND ACTIVITY SECTION 10.

Chemical Stability Product is considered stable under normal storage and handling conditions.

ARMOURZINC 110 Resene Paints Limited Page 2 of 4

Conditions to Avoid Freezing, excessive heat and changes in temperature Incompatible Materials Hazardous decomposition product Oxides of carbon and hydrogen

Hazardous reactions Hazardous polymerisation will not occur.

ARMOURZINC 110

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component Oral:LD50 mg/k Dermal:LD50 mg/k Inhale:LC50 pp

SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment

No data available for this product

Component Fish:LC50 mg/Lt BCF:<100 Kow

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number 1263

Proper Shipping Name Paint related product

Subsidiary Risk Poison Schedule

Packing Group: III

Class 3

HAZCHEM Code 3[Y]

Special precautions for user

SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants - Flammable

Approved Handler Not required

SECTION 16. OTHER INFORMATION

Date of Preparation 31/10/13

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commission

TWA Time weighted average STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry number

TLV Threshold limit value

Marine Pollutant Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations