

Technical Data Sheet
Issued, 01.09.09
FB 5-021 F02 Rev. 1



DINITROL® 6100
Spray Filler AC Spray

Characteristics:

DINITROL 6100 Spray Filler is an acrylic resin-based filler in aerosol packaging. The product has excellent filling properties, dries quickly, is easy to file and can be used with most repair lacquers.

Application:

DINITROL 6100 is used to level scratches, scrapes and other minor damage to paintwork.

Method of Use:

The surface to be treated must be clean and free from oil and grease. File all surrounding edges with fine sandpaper. Cover all areas which are not to be treated. Finely spray product in a cross coat at a distance of 20 – 30 cm. If required, repeat the process after the former coat is dry. Once dry, the filler can be filed and painted.

If the filler is applied in a fine layer as a primer, the surface need not be filed before painting.

Technical data:

Base:	Acrylic resin
Colour:	Light grey
Density:	Approx. 0.82 g/cm³
Flash point:	< - 18°C
Propellant:	Propane/butane
Package size:	400 ml
Storage time:	24 months (between 15° and 25°)

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmont Str. 76
D-32676 Lügde
Telephone:
+49 (0) 52 81 / 9 82 98-0
Fax:
+49 (0) 52 81 / 9 82 98-60
Email:
service@dinol.com