



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *DINITROL 8520 Lackspray schwarz seidenmatt AC*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the preparation** *Lacquer*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*DINOL GmbH  
Pyrmonter Str. 76  
D-32676 Lügde  
Tel: +49 5281 9829 80  
Fax: +49 5281 9829 860  
E-mail: msds@dinol.com*
- **Further information obtainable from:** *Research & Development*
- **1.4 Emergency telephone number:** *Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.*

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  *Xi; Irritant*  
*R36: Irritating to eyes.*
-  *F+; Extremely flammable*  
*R12: Extremely flammable.*
- *R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.*
- **Information concerning particular hazards for human and environment:**  
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*  
*At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.*  
*Warning! Pressurized container.*  
*Has a narcotizing effect.*
- **Classification system:**  
*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*
- **2.2 Label elements**
- **Labelling according to EU guidelines:**  
*The product has been marked in accordance with EU Directives / respective national laws.*  
*The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.*  
*The R and S phrases may be omitted if packaging contains no more than 0.125 litre.*
- **Code letter and hazard designation of product:**  
*Xi Irritant*  
*F+ Extremely flammable*
- **Risk phrases:**  
*12 Extremely flammable.*  
*36 Irritating to eyes.*  
*66 Repeated exposure may cause skin dryness or cracking.*

(Contd. on page 2)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 1)

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 2 Keep out of the reach of children.  
 16 Keep away from sources of ignition - No smoking.  
 23 Do not breathe vapour/spray.  
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
 46 If swallowed, seek medical advice immediately and show this container or label.  
 51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· **Classification in accordance with Directive 75/324/EEC: Extremely flammable**

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**























- **PBT:** Not applicable.  
 · **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with additions.

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone  Xi R36;  F R11 R66-67  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate R10-66-67  Flam. Liq. 3, H226;  STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9	Propane liquefied  F+ R12  Flam. Gas 1, H220;  Press. Gas, H280	10-<25%
CAS: 106-97-8 EINECS: 203-448-7	Butane, pure  F+ R12  Flam. Gas 1, H220;  Press. Gas, H280	10-<25%
CAS: 9004-70-0	Cellulose nitrate  F R11  Expl. 1.1, H201	1-<5%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene, mixed isomers, pure  Xn R20/21;  Xi R38 R10  Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-<5%
CAS: 141-78-6 EINECS: 205-500-4	Ethyl acetate  Xi R36;  F R11 R66-67  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	1-<5%

(Contd. on page 3)

Trade name: **DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 2)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After skin contact:** If skin irritation continues, consult a doctor.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
Headache  
Dizziness
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Carbon monoxide (CO)  
Nitrogen oxides (NO<sub>x</sub>)
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Absorb liquid components with liquid-binding material.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 3)

Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility: Not required.**

· **Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s) No further relevant information available.**

**SECTION 8: Exposure controls/personal protection**

· **Additional information about design of technical facilities: No further data; see item 7.**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**67-64-1 Acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**123-86-4 n-Butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**106-97-8 Butane, pure**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

**1330-20-7 Xylene, mixed isomers, pure**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**141-78-6 Ethyl acetate**

WEL Short-term value: 400 ppm  
Long-term value: 200 ppm

· **DNELs**

**67-64-1 Acetone**

Dermal	Long-term - systemic effects, worker	186 mg/kg bw/day (Worker)
Inhalative	Acute - Local effects, worker	2420 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects, worker	1210 mg/m <sup>3</sup> (Worker)

(Contd. on page 5)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 4)

**123-86-4 n-Butyl acetate**

Inhalative	Acute - Local effects, worker	960 mg/m <sup>3</sup> (Worker)
	Acute - local effects, general population	859.7 mg/m <sup>3</sup> (General Population)
	Acute - systemic effects, general population	859.7 mg/m <sup>3</sup> (General Population)
	Acute - systemic effect, worker	960 mg/m <sup>3</sup> (Worker)
	Long-term - local effects, general population	102.34 mg/m <sup>3</sup> (General Population)
	Long-term - local effects, worker	480 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects, general population	102.34 mg/m <sup>3</sup> (General Population)
	Long-term - systemic effects, worker	480 mg/m <sup>3</sup> (Worker)

· **PNECs****67-64-1 Acetone**

Aquatic compartment - marine water	1.06 mg/L (not specified)
Aquatic compartment - sediment in freshwater	30.4 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	3.04 mg/kg sed dw (not specified)
Terrestrial compartment - soil	29.5 mg/kg dw (not specified)

**123-86-4 n-Butyl acetate**

Aquatic compartment - freshwater	0.18 mg/L (not specified)
Aquatic compartment - marine water	0.018 mg/L (not specified)
Aquatic compartment - sediment in freshwater	0.981 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	0.0981 mg/kg sed dw (not specified)
Aquatic compartment - water, intermittent releases	0.36 mg/L (not specified)
Sewage treatment plant	35.6 mg/L (not specified)
Terrestrial compartment - soil	0.0903 mg/kg dw (not specified)

· **Ingredients with biological limit values:****1330-20-7 Xylene, mixed isomers, pure**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:** Protective gloves and protective skin cream· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 5)

Fluorocarbon rubber (Viton)

Nitrile rubber

· **Penetration time of glove material**

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:** Strong material gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Black

· **Odour:** Ester-like

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** < -20 °C (DIN 53213)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 365 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 13.0 Vol %

· **Vapour pressure At 20 °C:** 4000 hPa

· **Density At 20 °C:** 0.763 g/cm<sup>3</sup> (DIN 51757)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 7)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 6)

· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	86.0 %
· <b>Solids content:</b>	
	14.0 % (DIN 53216)
· <b>9.2 Other information</b>	
	No further relevant information available.
· <b>VOC (EU):</b>	86.50 %
· <b>VOC (EU):</b>	660.0 g/l
· <b>VOCV:</b>	86.50 %

### SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**67-64-1 Acetone**

Oral	LD50	5800 mg/kg (RAT)
Dermal	LD50	20000 mg/kg (RABBIT)

**123-86-4 n-Butyl acetate**

Oral	LD50	10760 mg/kg (RAT)
Dermal	LD50	>14000 mg/kg (RABBIT)
Inhalative	LC50/4 h	>20 mg/l (RAT)
	LC50/96 h	18 mg/l (pimephales promelas)

**106-97-8 Butane, pure**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**1330-20-7 Xylene, mixed isomers, pure**

Oral	LD50	8700 mg/kg (RAT)
Dermal	LD50	2000 mg/kg (RABBIT)
Inhalative	LC50/4 h	6350 mg/l (RAT)

**141-78-6 Ethyl acetate**

Oral	LD50	4935 mg/kg (RABBIT)
Inhalative	LC50/4 h	1600 mg/l (RAT)

- **Primary irritant effect:**
- **on the skin:** The product degreases the skin.

(Contd. on page 8)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 7)

- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

##### 123-86-4 n-Butyl acetate

EC50/48 h	44 mg/l (DAPHNIA MAGNA)
EC50/72 h	647.7 mg/l (ALGAE)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** There is no data available for the product.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** There is no data available for the product.
- **Remark:** The effects in aquatic environment are not known.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing dangerous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by dangerous substances
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

(Contd. on page 9)





**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 8)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |                            |
|---|----------------------------|
| · <b>14.1 UN-Number</b><br>· <b>ADR, IMDG, IATA</b>   | UN1950                     |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR</b><br>· <b>IMDG, IATA</b>  | 1950 AEROSOLS<br>AEROSOLS  |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR</b>  |                            |
|                                    |                            |
| · <b>Class</b><br>· <b>Label</b>  | 2 5F Gases.<br>2.1         |
| · <b>IMDG, IATA</b>   |                            |
|                                   |                            |
| · <b>Class</b><br>· <b>Label</b>  | 2 Gases.<br>2.1            |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>   | Void                       |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>  | No                         |
| · <b>14.6 Special precautions for user</b><br>· <b>EMS Number:</b>  | Warning: Gases.<br>F-D,S-U |
| · <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>                               | Not applicable.            |
| · <b>Transport/Additional information:</b>  |                            |
| · <b>ADR</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Transport category</b><br>· <b>Tunnel restriction code</b> | 1L<br>2<br>D               |

GB

(Contd. on page 10)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 9)

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to EU guidelines:**  
The product has been marked in accordance with EU Directives / respective national laws.  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.  
The R and S phrases may be omitted if packaging contains no more than 0.125 litre.
- **Code letter and hazard designation of product:**  
Xi Irritant  
F+ Extremely flammable
- **Risk phrases:**  
12 Extremely flammable.  
36 Irritating to eyes.  
66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**  
2 Keep out of the reach of children.  
16 Keep away from sources of ignition - No smoking.  
23 Do not breathe vapour/spray.  
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
46 If swallowed, seek medical advice immediately and show this container or label.  
51 Use only in well-ventilated areas.
- **Special labelling of certain preparations:**  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Buildup of explosive mixtures possible without sufficient ventilation.
- **Classification in accordance with Directive 75/324/EEC: Extremely flammable**
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
NK	86.5
- **Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.**
- **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H201 Explosive; mass explosion hazard.  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H312 Harmful in contact with skin.

(Contd. on page 11)

**Trade name: DINITROL 8520 Lackspray schwarz seidenmatt AC**

(Contd. of page 10)

- H315 Causes skin irritation.*  
*H319 Causes serious eye irritation.*  
*H332 Harmful if inhaled.*  
*H336 May cause drowsiness or dizziness.*  
*R10 Flammable.*  
*R11 Highly flammable.*  
*R12 Extremely flammable.*  
*R20/21 Harmful by inhalation and in contact with skin.*  
*R36 Irritating to eyes.*  
*R38 Irritating to skin.*  
*R66 Repeated exposure may cause skin dryness or cracking.*  
*R67 Vapours may cause drowsiness and dizziness.*

- **Department issuing MSDS:** Research & Development
- **Contact:** Kontakt: [msds@dinol.com](mailto:msds@dinol.com) oder Tel.: 0049 (0)5281 982 980
- **\* Data compared to the previous version altered.**