

1. Identification of the substance/mixture and of the company/undertaking

Product name	389S Imron Accelerator
Product code	389S
Intended use of the substance/preparation	Intermediate
Supplier	Axalta Coating Systems Australia Pty Limited
Street address	15 - 23 Melbourne Road, Riverstone NSW 2765, Australia
Telephone	
Telefax	
Emergency Information	
Emergency telephone number	+(64) 9801 0034 NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248
Importer	Resene Automotive & Light Industrial
Street/Box	4 Te Apunga Place, Mt Wellington, Auckland, NZ
Nat.-Code/Postal code/City	
Telephone	+64 (09) 259 2738
Date of preparation	2015-01-29

2. Hazards identification

Classified as a Dangerous Good according to NZS 5433
Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

HSNO Classification

Flammable liquids	Category 3.1C
Acute oral toxicity	Category 6.1D
Skin corrosion/irritation	Category 6.3B
Serious eye damage/eye irritation	Category 6.4A
Skin sensitisation	Category 6.5B
Germ cell mutagenicity	Category 6.6B
Toxicity for reproduction	Category 6.8A
Target Organ Systemic Toxicant - Single exposure	Category 6.9B
Target Organ Systemic Toxicant - Repeated exposure	Category 6.9B
Acute aquatic toxicity	Category 9.1C
Chronic aquatic toxicity	Category 9.1C

Endpoints which are ""not classified"", ""cannot classified"" and ""not applicable"" are not shown

GHS-Labeling

Hazard symbols	
Signal word	Danger
Hazard statements	<p>Harmful in contact with skin. Suspected of causing genetic defects. Flammable liquid and vapour. Harmful to aquatic life. Harmful to aquatic life with long lasting effects. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction.</p>

Causes mild skin irritation.
Causes serious eye irritation.
Toxic if swallowed or if inhaled

Precautionary statements

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
Wash hands after handling.
Do not eat, drink or smoke when using this product.
Store locked up.
Dispose of contents/container in accordance with local regulations.
Specific treatment (see supplemental first aid instructions on this label).
Wear protective gloves/ protective clothing.
Avoid breathing dust/ vapours/ spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Store in a well-ventilated place. Keep container tightly closed.
Use only outdoors or in a well-ventilated area.
Obtain special instructions before use.
IF exposed or concerned: Get medical advice/ attention.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Wear protective gloves/ eye protection/ face protection.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Store in a well-ventilated place. Keep cool.
Avoid release to the environment.
Contaminated work clothing should not be allowed out of the workplace.
If skin irritation or rash occurs: Get medical advice/ attention.

Other hazards which do not result in classification

None known.

3. Composition/information on ingredients**Pure substance/mixture**

Mixture

CAS-No.	Chemical Name	Concentration	GHS	Haz- ardous
123-54-6	pentane-2,4-dione	90 - 100%	✓	
77-58-7	dibutylbis((1-oxododecyl)oxy)stannane	0.3 - 1.0%	✓	

Non-regulated ingredients 0.0 - 0.1%

4. First aid measures**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed**Inhalation**

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see MSDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. If this product is mixed with an isocyanate, skin contact may cause sensitization.

Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons

High volume water jet

Specific hazards

Flammable liquid. Vapours may form explosive mixtures with air. Remove all sources of ignition. Solvent vapours are heavier than air and may spread along floors. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. Handling and storage

Handling

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

Storage

Suitable storage conditions

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

8. Exposure controls/personal protection

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

National occupational exposure limits

Workplace Exposure Standards (WESs) 2002

Chemical Name		
dibutylbis((1-oxododecyl)oxy)stannane	STEL	0.2 mg/m ³
	TWA	0.1 mg/m ³

Engineering measures

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Eye protection

Wear protective eyewear for protection against solvent spatter.

Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical Name	Glove material	Glove thickness	Break through time
pentane-2,4-dione	butyl-rubber	0.7 mm	480 m

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to

use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

9. Physical and chemical properties

Appearance

Form : liquid Colour: clear Odour: Characteristic Paint Odor Odor Threshold : no data available

pH	No data available.	
Freezing point	Not applicable.	
Boiling point	135 °C	
Flash point	29 °C	
Evaporation rate	Slower than Ether	
Flammability		
Upper explosion limit	11.6 %	
Lower explosion limit	1.7 %	
Vapour pressure	8.9 hPa	
Solubility(ies)	appreciable	
Vapour density	no data available	
Density	0.98 g/cm ³	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	350 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	Not applicable.	ISO 2431-1993

10. Stability and reactivity

Stability

Stable

Hazardous polymerisation

Will not occur.

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see MSDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:**Acute oral toxicity**

pentane-2,4-dione	Category 4
dibutylbis((1-oxododecyl)oxy)stannane	Category 2

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition 0 %

Skin corrosion/irritation

pentane-2,4-dione	Category 3
dibutylbis((1-oxododecyl)oxy)stannane	Category 1B

Serious eye damage/eye irritation

pentane-2,4-dione	Category 2A
dibutylbis((1-oxododecyl)oxy)stannane	Category 1

Respiratory sensitisation

Not classified according to GHS criteria

Skin sensitisation

pentane-2,4-dione	Category 1
dibutylbis((1-oxododecyl)oxy)stannane	Category 1

Germ cell mutagenicity

pentane-2,4-dione	Category 2
dibutylbis((1-oxododecyl)oxy)stannane	Category 2

Carcinogenicity

Not classified according to GHS criteria

Toxicity for reproduction

dibutylbis((1-oxododecyl)oxy)stannane Category 1A

Target Organ Systemic Toxicant - Single exposure• **Inhalation****Central nervous system** pentane-2,4-dione**Target Organ Systemic Toxicant - Repeated exposure**• **Skin Absorption****Central nervous system** pentane-2,4-dione**Aspiration toxicity**

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. Ecological information

Product contains environmentally hazardous substances and product is not classified per GHS.

Ecotoxicity effects

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

Acute aquatic toxicity

pentane-2,4-dione	Category 3
dibutylbis((1-oxododecyl)oxy)stannane	Category 1

Chronic aquatic toxicity

pentane-2,4-dione	Category 3
dibutylbis((1-oxododecyl)oxy)stannane	Category 1

% of unknown composition 0%

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in soil

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste disposal methods**

Dispose of in accordance with local regulations.

Disposal considerations

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

14. Transport information**NZS5433**

Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S.
(pentane-2,4-dione; dibutylbis((1-oxododecyl)oxy)stannane)

UN number: 1992
Hazard Class: 3
Packing group: III
Hazchem Code: 3W

IMDG (Sea transport)

Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S.
(pentane-2,4-dione; dibutylbis((1-oxododecyl)oxy)stannane)

UN number: 1992
Hazard Class: 3
Subsidiary Hazard Class: 6.1
Packing group: III
Marine Pollutant: no
EmS: F-E,S-D

ICAO/IATA (Air transport)

Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S.
(pentane-2,4-dione; dibutylbis((1-oxododecyl)oxy)stannane)

UN number: 1992
Hazard Class: 3
Subsidiary Hazard Class: 6.1
Packing group: III

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information**National regulatory information**

HSNO Approval Code	HSR002662
HSNO Classification	
Acute oral toxicity	Category 6.1D
Skin corrosion/irritation	Category 6.3B
Serious eye damage/eye irritation	Category 6.4A
Skin sensitisation	Category 6.5B
Germ cell mutagenicity	Category 6.6B
Toxicity for reproduction	Category 6.8A
Target Organ Systemic Toxicant - Single exposure	Category 6.9B
Target Organ Systemic Toxicant - Repeated exposure	Category 6.9B
Flammable liquids	Category 3.1C
Acute aquatic toxicity	Category 9.1C
Chronic aquatic toxicity	Category 9.1C



16. Other information

Revision Note

Version	Changes
1.1	2, 7, 8, 11

Revision Date: 2015-01-29
B10360367

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet