

## 1. Identification of the substance/mixture and of the company/undertaking

Product name	Abcite® X60 Light Blue (RAL 5012)		
Product code	9148-33		
Intended use of the substance/preparation Thermoplastic coating powder			
<b>Supplier</b> Street address Telephone Telefax	Axalta Coating Systems Australia Pty Limited 15 - 23 Melbourne Road, Riverstone NSW 2765, Australia		
Emergency Information Emergency telephone number	+(64) 9801 0034 NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248		
Importer	Resene Automotive & Light Indus- trial		
Street/Box	4 Te Apunga Place, Mt Wellington, Auckland, NZ		
NatCode/Postal code/City Telephone	+64 (09) 259 2738		
Date of preparation	2015-01-29		

## 2. Hazards identification

Not classified as a Dangerous Good under NZS 5433 Not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

## **HSNO Classification**

Not classified according to GHS criteria

## GHS-Labelling

Hazard symbols	Not classified according to GHS criteria
Signal word	Not classified according to GHS criteria
Hazard statements	Not classified according to GHS criteria
Precautionary statements	Not classified according to GHS criteria

Other hazards which do not result in classification Safety data sheet available for professional user on request.

## 3. Composition/information on ingredients

Pure substance/mixture Mixture

CAS-No.	Chemical Name	Concentration	GHS Haz- ardous
7631-86-9	amorphous Silica	0.3 - 1.0%	

Non-regulated ingredients 90 - 100%

© 2014 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.



## 4. First aid measures

## Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

## Skin contact

Do NOT use solvents or thinners. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

## Inhalation

Avoid breathing dust. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

## Ingestion

If swallowed, seek medical advice immediately and show this container or label.

## Most Important Symptoms/effects, acute and delayed

## Inhalation

Dust generated from this product may be irritating to the respiratory tract.

## Ingestion

May result in gastrointestinal distress.

## Skin or eye contact

Dust generated from this product may cause irritation of the eyes. Repeated or prolonged contact may cause skin irritation with discomfort and dermatitis.

## Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

# 5. Firefighting measures

## Suitable extinguishing media

Water sprayDry chemical

## Extinguishing media which shall not be used for safety reasons

High volume water jet

## Specific hazards

The product is not flammable. Do not allow run-off from fire fighting to enter drains or water courses. Always keep in containers of same material as the original one.

## Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary.

## 6. Accidental release measures

## **Personal precautions**

Keep away from sources of ignition. Air out the room. Do not breathe dust. Comply with safety directives (see chapters 7 and 8).

## **Environmental precautions**

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

## Methods for cleaning up

Contain and collect spillage with a electrically protected vacuum cleaner or by wet brushing and place in container for disposal according to local regulations. Do not use a dry brush as dust clouds or static can be created! Use a suitable vacuum cleaner.



# 7. Handling and storage

## Handling

Persons suffering from respiratory problems or allergic responses should not be exposed to, or handle, powder coatings!

#### Safe handling advice

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. Keep away from open flames, hot surfaces and sources of ignition. Smoking, eating and drinking should be prohibited in the application area. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.

#### Storage

#### Suitable storage conditions

Observe label precautions. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

## 8. Exposure controls/personal protection

## National occupational exposure limits Workplace Exposure Standards (WESs) 2002

Chemical Name amorphous Silica

TWA 10 mg/m3

#### **Engineering measures**

Do not breathe dust. Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.

#### **Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

#### **Respiratory protection**

If dust formation exceeds the air concentration limits, then a respiratory protection device approved for this purpose must be worn.

#### Eye protection

Eye protection (to EN 166/170) designed to protect against exposure to dusts should be worn when there is a likelihood of exposure.

#### Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Glove material	Glove thickness	Break through time
Nitrile rubber	0.33 mm	> 240 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.



## Skin and body protection

Wear suitable protective clothing. Care should be taken in the selection of protective clothing. Avoid contact with the powder on throat and wrists due to possible inflammation and irritation of the skin.

## Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

## 9. Physical and chemical properties

## Appearance

Form : solid Colour: blue Odor Threshold : no data available

рН	not applicable	
Freezing point	Not applicable.	
Boiling point	Not applicable.	
Flash point	Not applicable.	
Evapouration rate	not applicable	
Flammability		
Upper explosion limit	Not applicable.	
Lower explosion limit	Not applicable.	
Vapour pressure	0.0 hPa	
Solubility(ies)	nil	
Vapour density	no data available	
Density	$0.95 \ g/cm^{3}$	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	Not applicable.	DIN 51794
Decomposition temperature		
Viscosity (23 ° C)	Not applicable.	ISO 2431-1993

Does not sustain combustion.

# 10. Stability and reactivity

### Stability Stable

Stable

## Hazardous polymerisation

Will not occur.

## Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

## Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

## Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

## Information on likely routes of exposure

## Inhalation

Dust generated from this product may be irritating to the respiratory tract.

## SAFETY DATA SHEET



**Ingestion** May result in gastrointestinal distress.

#### Skin or eye contact

Dust generated from this product may cause irritation of the eyes. Repeated or prolonged contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity Not classified according to GHS criteria

Acute dermal toxicity Not classified according to GHS criteria

Acute inhalation toxicity Not classified according to GHS criteria

Skin corrosion/irritation

Not classified according to GHS criteria

Serious eye damage/eye irritation Not classified according to GHS criteria

Respiratory sensitisation Not classified according to GHS criteria

Skin sensitisation Not classified according to GHS criteria

## Germ cell mutagenicity

Not classified according to GHS criteria

Carcinogenicity Not classified according to GHS criteria

**Toxicity for reproduction** Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure Not classified according to GHS criteria

Target Organ Systemic Toxicant - Repeated exposure Not classified according to GHS criteria

Aspiration toxicity Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc. ) No information available.

Symptoms related to the physical, chemical and toxicological characteristics No information available.

# 12. Ecological information

Product does not contain any environmentally hazardous substances and product is not classified per GHS



### **Ecotoxicity effects**

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

**Persistence and degradability** No information available.

**Bioaccumulation** No information available.

**Mobility in soil** No information available.

Other adverse effects

No information available.

## **13. DISPOSAL CONSIDERATIONS**

#### Waste disposal methods

Dispose of in accordance with local regulations.

## **Disposal considerations**

A disposal process that converts the waste into energy is recommended. Can be landfilled or incinerated, when in compliance with local regulations.

## 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

## Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

## 15. Regulatory information

### National regulatory information

HSNO Approval Code HSR002670 HSNO Classification

## 16. Other information

**Revision Note** 

Version	Changes
1.0	
Revision Date: B12941287	2015-01-29

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet