

# SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** RALI 440 INDUSTRIAL PRIMER REDUCER

**Other Names:**

**Recommended Use:** Paint thinner

**Company Name:** Resene Paints Limited New Zealand

**Address:** 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND  
P O Box 38242, Wellington Mail Centre

**Phone:** (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia

**Address** 7 Production Avenue, Molendinar, Queensland 4214  
P O Box 924, Beenleigh, Queensland 4207  
AUSTRALIA

**Phone** 1800 738 38

**Emergency Telephone:**

**New Zealand** 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

**New Zealand Poisons Centre: 0800 764 766**

**Australia** 1800 738 383

**Australian Poisons Centre: 131 126**

## SECTION 2. HAZARDS IDENTIFICATION

**Hazard Classification** HAZARDOUS according to NZ HSNO Regulations  
Regulated under NZS5433 for land transportation

**Risk Phrases** Not assigned

**Safety Phrases** Not assigned

**Substance Classification** 3.1C 6.1D 6.3A 6.4A 6.8B 6.9B 9.1D 9.3C

**Hazard Statements** Highly flammable liquid and vapour  
Harmful if swallowed  
Causes skin irritation  
Causes eye irritation  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Causes long lasting harmful effects to the aquatic environment  
Harmful to terrestrial vertebrates

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENT

Ingredients	%	CAS No	TWA	
Methyl Ethyl Ketone	30-60	78-93-3	445 mg/m <sup>3</sup>	NZ OSH (WES) 2002
Methyl benzene	30-60	108-88-3	188 mg/m <sup>3</sup>	NZ OSH (WES) 2002

## SECTION 4. FIRST AID MEASURES

**Eyes** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention/advice.

**Swallowed:** Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel unwell.

**Skin** IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Inhaled** Remove to fresh air and keep at rest in a position comfortable for breathing.

**Aggravated medical conditions caused by exposure**

**Chronic Health Effects** Not Identified

**Advice to Doctor** Treat symptomatically

## SECTION 5. FIRE FIGHTING MEASURES

**Extinguisher** Foam, Carbon Dioxide, Dry Chemical

**Hazards from combustion products**

**Special protective precautions and equipment for firefighters****Fire/Explosion Hazard****Auto Ignition Temperature****Lower Explosion Limit****Upper Explosion Limit****Hazchem Code**    **Flash Point**

3[Y]E

4°C

**SECTION 6. ACCIDENTAL RELEASE MEASURES****Emergency Procedures**

Keep spectators away and avoid breathing dust or vapours

**Methods and materials for containment and clean up****Minor Spills** Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

**Major Spills** Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

**SECTION 7. HANDLING AND STORAGE****Precautions for safe handling** Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities

**Storage Temperatures**    **Min** 1°C**Max** 40°C

Incompatibilities

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****National exposure standards for mixture** No exposure standards has been established for this product**Component****Breathing Zone ppm****Breathing Zone mg/m<sup>3</sup>****Personal Protection****Eye:** Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using any paint.**Hands/Feet** Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet recommended.**Other** Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of heated materials. Wash hands thoroughly before handling food.

**Respirator** None required**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance** Clear liquid

Odour    pH    Vapour Pressure    Vapour Density    Boiling Point    Melt Freeze

Solubility

Volatile by Weight

Immiscible

100

**SECTION 10. STABILITY AND ACTIVITY****Chemical Stability** Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Materials

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

**SECTION 11. TOXICOLOGICAL INFORMATION**

No data available for this product

Component	Oral:LD50 mg/k	Dermal:LD50 mg/k	Inhale:LC50 pp
-----------	----------------	------------------	----------------

**SECTION 12. HAZARDS IDENTIFICATION**

No data available for this product

Do not allow the product to enter the environment

Component	Fish:LC50 mg/Lt	BCF:<100 Kow
-----------	-----------------	--------------

**SECTION 13. DISPOSAL CONSIDERATIONS**

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

**SECTION 14. TRANSPORT INFORMATION**

Transport only in accordance with the following regulations

UN Number	1263
Proper Shipping Name	Paint related product
Subsidiary Risk	
Poison Schedule	
Packing Group:	II
Class	3
HAZCHEM Code	3{Y}E

**Special precautions for user****SECTION 15. REGULATORY INFORMATION**

Group Standard HSR002662 Surface Coatings &amp; Colourants (Flammable)

Approved Handler Class 3.1b required for quantities greater than 250Lt (containers greater than 5Lt capacity) or greater than 500Lt (containers less than 5Lt capacity)

**SECTION 16. OTHER INFORMATION**

Date of Preparation	13/04/11
Literature references	MSDS's for individual raw material

**Abbreviations:**

NOHSC	National Occupational Health and Safety Commission
TWA	Time weighted average
STEL	Short term exposure limit
CAS Numbe	Chemical Abstract Service registry number
TLV	Threshold limit value
Marine Pollutant	Marine Pollutant <input type="checkbox"/>

**Safety data sheets are updated frequently. Please ensure that you have a current copy**

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.