

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: RALI ENGINE DEGREASER

Other Names:

Recommended Use:

Company Name: Resene Paints Limited New Zealand **Address:** 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND
P O Box 38242, Wellington Mail Centre

Phone: (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia **Address** 7 Production Avenue, Molendinar, Queensland 4214
P O Box 785, Ashmore City, Queensland 4214
AUSTRALIA

Phone 1800 738 383

Emergency Telephone:

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

Australian Poisons Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations
Regulated under NZS5433 for land transportation

Risk Phrases Not assigned

Safety Phrases Not assigned

Substance Classification 3.1C 6.1D 6.3A 6.8B 6.9B 8.3A 9.1B

Hazard Statements Flammable liquid and vapour
Harmful if swallowed
Causes skin irritation
Suspected of damaging fertility or the unborn child.
Suspected of damaging organs through prolonged or repeated exposure
Causes respiratory irritation
Causes serious eye damage
Toxic to aquatic life with long lasting effects

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	%	CAS No	TWA	
Kerosene	>60	8008-20-6	5 mg/m ³	NZ OSH (WES) 2002
Aromatic Hydrocarbon	10-30	64742-82-1	525 mg/m ³	
C9 alkylphenol ethoxylate, branched	1-10	68412-54-4	None Establish	
Nonylphenol ethoxylate	1-10	9016-45-9	None Establish	

SECTION 4. FIRST AID MEASURES

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Rinse mouth. DO NOT induce vomiting.
Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel unwell.

Skin Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and plenty of soap. If skin irritation occurs get medical advice/attention.

Inhaled Remove to fresh air and keep at rest in a position comfortable for breathing.

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified

Advice to Doctor Treat Symptomatically

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard	Auto Ignition Temperature	Lower Explosion Limit	Upper Explosion Limit
Hazchem Code 3[Y]	Flash Point 36°C	231°C	0.7% 5.3%

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Ventilate area, avoid breathing of vapours.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Remove all ignition sources.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities

Storage Temperatures Min 0°C Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure standards for mixture No exposure standards has been established for this product

Component	Breathing Zone ppm	Breathing Zone mg/m³
------------------	---------------------------	--

Personal Protection

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet recommended.

Other Use in well ventilated area with explosion proof equipment. When added to other components mixed material presents hazards from all components.

Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of heated materials. Wash hands thoroughly before handling food.

Respirator None required

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze

Hydrocarbon n/a 1.5 kPa 4.5 150-159°C

Solubility
Insoluble

Volatile by Weight
88

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Materials Avoid storing with strong oxidisers, acids and alkalis

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component	Oral:LD50 mg/k	Dermal:LD50 mg/k	Inhale:LC50 pp
-----------	----------------	------------------	----------------

SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment

No data available for this product

Component	Fish:LC50 mg/Lt	BCF:<100 Kow
-----------	-----------------	--------------

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Triple rinse the empty container until clean. Recycle washings where appropriate. Puncture can to prevent re-use empty can in approved landfill. Do not allow washings to enter waterways

SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number	1263
Proper Shipping Name	Paint related product
Subsidiary Risk	
Poison Schedule	
Packing Group:	III
Class	3 - Flammable liquid
HAZCHEM Code	3[Y]

Special precautions for user**SECTION 15. REGULATORY INFORMATION**

Group Standard HSR002662 Surface Coatings & Colourants - Flammable

Approved Handler None required

SECTION 16. OTHER INFORMATION

Date of Preparation	30/05/2012
Literature references	MSDS's for individual raw material
Abbreviations:	
NOHSC	National Occupational Health and Safety Commission
TWA	Time weighted average
STEL	Short term exposure limit
CAS Number	Chemical Abstract Service registry number
TLV	Threshold limit value
Marine Pollutant	Marine Pollutant <input checked="" type="checkbox"/>

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.