RALI EUROSPEED Version Number: 3

# SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: RALI EUROSPEED

Other Names:

Recommended Use: Part A of a 2-pack acrylic topcoat

Company Name: Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND

P O Box 38242, Wellington Mail Centre

**Phone:** (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214

P O Box 785, Ashmore City, Queensland 4214

AUSTRALIA

**Phone** 1800 738 383

**Emergency Telephone:** 

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

**Australian Poisons Centre: 131 126** 

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Regulated under NZS5433 for land transportation

Risk Phrases Not assigned Safety Phrases Not assigned

**Substance Classification** 3.1B 6.1D 6.3A 6.4A 6.8A 6.9B 9.1C

**Hazard Statements** Highly flammable liquid and vapour

Harmful if swallowed Causes skin irritation Causes eye irritation

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	%	CAS No	TWA	
Methyl benzene	30-60	108-88-3	188 mg/m³	NZ OSH (WES) 2002
Propylene glycol monomethyl ether acetate	1-10	108-65-6	None Establish	
Amorphous silica	1-10	112945-52-5	Not Known	
Methyl Ethyl Ketone	1-10	78-93-3	445 mg/m <sup>3</sup>	NZ OSH (WES) 2002
Non-Hazardous material	10-30	Not known	None Establish	

### SECTION 4. FIRST AID MEASURES

**Eyes** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel

unwell.

**Skin** Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and

plenty of soap. If skin irritation occurs get medical advice/attention.

Inhaled IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified

Advice to Doctor Treat Symptomatically

## SECTION 5. FIRE FIGHTING MEASURES

RALI EUROSPEED Page 1 of 4 Resene Paints Limited

**Extinguisher** Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

Hazchem Code Flash Point

3[Y]E 4°C

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### **Emergency Procedures**

Keep spectators away and avoid breathing dust or vapours

### Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

## SECTION 7. HANDLING AND STORAGE

**Precautions for safe handling** Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities

Storage Temperatures Min 0°C Max 40°C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure

No exposure standards has been established for this product

standards for mixture

Component Breathing Zone ppm Breathing Zone mg/m<sup>3</sup>

### **Personal Protection**

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using

any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet

recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

**Respirator** None required

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Coloured viscous liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze
Solubility

Hydrocarbon Solubility Volatile by Weigh Immiscible 47

## SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Materials

Hazardous decomposition product Oxides of carbon and hydrogen

RALI EUROSPEED Page 2 of 4 Resene Paints Limited

Hazardous reactions Hazardous polymerisation will not occur.

### RALI EUROSPEED

#### TOXICOLOGICAL INFORMATION SECTION 11.

No data available for this product

Component Inhale:LC50 pp Oral:LD50 mg/k Dermal:LD50 mg/k

#### SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

Component Fish:LC50 mg/Lt BCF:<100 Kow

#### **DISPOSAL CONSIDERATIONS** SECTION 13.

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

#### TRANSPORT INFORMATION SECTION 14.

Transport only in accordance with the following regulations

**UN Number** 1263

Paint related product Proper Shipping Name

Subsidiary Risk

Poison Schedule

Packing Group: Ш

Class 3

**HAZCHEM Code** 3[Y]E

Special precautions for user

#### REGULATORY INFORMATION SECTION 15.

Group Standard Surface Coatings & Colourant - Flammable

Approved Handler Class 3.1B required for quantities greater than 250Lt (containers greater than 5Lt

capacity) or greater than 500Lt (containers less than 5Lt capacity)

#### SECTION 16. OTHER INFORMATION

Date of Preparation 9/07/2012

Literature references MSDS's for individual raw material

Abbreviations:

**NOHSC** National Occupational Health and Safety Commission

**TWA** Time weighted average Short term exposure limit STEL

Chemical Abstract Service registry number **CAS Number** 

Threshold limit value TLV

Marine Pollutant Marine Pollutant

#### Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations