1

SAFETY DATA SHEET

SECTION 1.	IDENTIFICATION OF	THE M	ATERIAL AND S	SUPPLIER
Product Name:	RALI FM1 AUTOPRIMER			
Other Names:				
Recommended Use:				
Company Name:	Resene Paints Limited New Zealand	Address:		ae, Wellington, NEW ZEALAND
Phone:	(04) 577 0500 Fax: (04) 577 0600		P U B0x 38242,	Wellington Mail Centre
	Resene Paints Limited Australia	Address	7 Production Avenue, Mole	
Phone	1800 738 383		P O Box 785, Ashmore AUST	City, Queensland 4214
Emergency Telepho	one:			
New Zealand	0800 737 363 Available I	Monday - F	riday 8.00am - 4.30p	m
	New Zealand Poisons C	entre: 080	0 764 766	
Australia	1800 738 383			
	Australian Poisons Cent	tre: 131 12	6	
SECTION 2.	HAZARDS IDENTIFIC	CATION		
Hazard Classificato			•	
	Regulated under NZS5433 fo	or land trans	sportation	
Risk Phrases	Not assigned			
Safety Phrases	Not assigned			
	cation 3.1B 6.1E 6.3A 6.4A 6.8B			
Hazard Statements	Highly flammable liquid and v	-		
	May be harmful in contact with	n skin		
	Causes skin irritation			
	Causes eye irritation		harra ahild	
	Suspected of damaging fertilit			
	May cause damage to organs	• •	•	•
	Causes long lasting harmful e		•	
SECTION 3.	COMPOSITION / INF	ORMAI	ION ON INGRE	DIENT
Ingredients	%	CAS No	D TWA	
Butyl Acetate (n-)	10-30	123-86-4	4 150ppm +	NZ OSH (WES) 2002
Methyl benzene	10-30	108-88-3	0	NZ OSH (WES) 2002
Dimethylbenzene	1-10	1330-20	•	NZ OSH (WES) 2002
Nitrocellulose	1-10	9004-70		
isopropanol	1-10	67-63-0	983 mg/m³	NZ OSH (WES) 1994

Non-Hazardous Material 10-30 Various FIRST AID MEASURES SECTION 4.

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Eyes Continue rinsing. If eye irritation persists get medical attention/advice. Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel Swallowed: unwell. Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and Skin plenty of soap. If skin irritation occurs get medical advice/attention.

68611-44-9

1333-86-4

Not Known

Not Known

None Establish

Remove to fresh air and keep at rest in a position comfortable for breathing. Inhaled

<1

<1

Aggravated medical conditions caused by exposure

Amorphous silica

CI Pigment Black 7

Chronic Health Effects Not Identified Advice to Doctor Treat Symptomatically

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

4

Special protective precautions and equipment for firefighters

Fire/Explosion HazardAuto Ingnition TemperatureLower Explosion LimitUpper Explosion LimitHazchem CodeFlash Pointn/a

3[Y]E

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water. Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities Not identified

Storage Temperatures Min 1°C Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

•	ational exposure No exposure standards has been established for this product andards for mixture				-		
Component		Brea	athing Zone ppm	Bre	eathing Zone mg/m ³		
Personal Pro	tection						
Eye:	Safety ey any paint		h guards or side s	hields to preve	nt eye contact	is recommend	ed when using
Hands/Feet	Protective recomme		s of neoprene or r	nitrile rubber - li	ndustrial weigh	t lined gauntle	t
Other	Overalls,	impervious clothi	ng, barrier cream,	eyewash unit,	skin cleansing	cream.	
	heated m	aterials. Wash h	personal cleanline ands thoroughly b			id breathing v	apours of
Respirator	None req	luired					
SECTION	9.	PHYSICAL A	AND CHEMIC	CAL PROP	ERTIES		
Appearance	Coloured	viscous liquid				_	
Odour hydrocarbon/ 미		apour Pressure n/a	Vapour Density heavier than air	Boiling Point 82°C	Melt Freeze 0°C	Solubility soluble	Volatile by Weigh 52
SECTION	10.	STABILITY	AND ACTIV	ITY			

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Materials

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

RALI FM1 AUTOPRIMER

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component

Oral:LD50 mg/k Dermal:LD50 mg/k

Inhale:LC50 pp

SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

Component

Fish:LC50 mg/Lt

BCF:<100 Kow

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number	1263
Proper Shipping Name	Paint related product
Subsidiary Risk	
Poison Schedule	
Packing Group:	II
Class	3
HAZCHEM Code	3[Y]E
Special precautions for u	Iser

SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants - Flammable

Approved Handler Class 3.1B required for quantities greater than 250Lt (containers greater than 5Lt capacity) or greater than 500Lt (containers less than 5Lt capacity)

SECTION 16.	OTHER INFORMATION
Date of Preparation	4/11/2010
Literature references	MSDS's for individual raw material
Abbreviations:	
NOHSC	National Occupational Health and Safety
TWA	Time weighted average
STEL	Short term exposure limit
CAS Numbe	Chemical Abstract Service registry numb
TLV	Threshold limit value
Marine Pollutant	Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.