RALI MULTIPURPOSE REDUCER

SAFETY DATA SHEET

SECTION 1.	IDENTIFICATION OF THE MATERIAL AND SUPPLIER
Product Name:	RALI MULTIPURPOSE REDUCER
Other Names:	
Recommended Use:	
Company Name:	Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND P O Box 38242, Wellington Mail Centre
Phone:	(04) 577 0500 Fax: (04) 577 0600
	Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214
Phone	P O Box 785, Ashmore City, Queensland 4214 AUSTRALIA
Emergency Teleph	one:
New Zealand	0800 737 363 Available Monday - Friday 8.00am - 4.30pm
	New Zealand Poisons Centre: 0800 764 766
Australia	1800 738 383
	Australian Poisons Centre: 131 126
SECTION 2.	HAZARDS IDENTIFICATION
Hazard Classificato	n HAZARDOUS according to NZ HSNO Regulations
	Regulated under NZS5433 for land transportation
Risk Phrases	Not assigned
Safety Phrases	Not assigned
Substance Classifie	cation 3.1B 6.1D 6.3A 6.4A 6.8B 6.9B 9.1C 9.3C
Hazard Statements	Highly flammable liquid and vapour
	Harmful if swallowed
	Harmful if inhaled
	Causes skin irritation
	Causes eye irritation
	Suspected of damaging fertility or the unborn child.
	May cause damage to organs through prolonged or repeated exposure.
	Toxic to aquatic life with long lasting effects
	Harmful to terrestrial invertebrates
SECTION 3.	COMPOSITION / INFORMATION ON INGREDIENTS
Ingredients	% CAS No TWA
Methyl benzene	30-60 108-88-3 188 mg/m ³ NZ OSH (WES) 2002
Acetone	10-30 67-64-1 1185 mg/m ³ NZ OSH (WES) 2002
n-Butyl Acetate	10-30 123-86-4 713 mg/m ³ ^{NZ OSH} (WES) ¹⁹⁹⁴
Dimethylbenzene	10-30 1330-20-7 217 mg/m ³ NZ OSH (WES) 2002

SECTION 4. FIRST AID MEASURES

Petroleum Naphtha, light hydrotreated

Methyl Ethyl Ketone

EyesRinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.
Continue rinsing. If eye irritation persists get medical attention/advice.Swallowed:Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel
unwell.SkinRemove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and
plenty of soap. If skin irritation occurs get medical advice/attention.InhaledIF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing

64742-49-0

78-93-3

10-30

1-10

Aggravated medical conditions caused by exposure

NZ OSH (WES) 2002

72 mg/m³ as h ^{OSHA}

445 mg/m³

Chronic Health Effects Not Identified

Advice to Doctor Treat Symptomatically

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit Hazchem Code Flash Point

3IYIE 4°C

3[Y]E

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water. Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities

Storage Temperatures Min 0°C Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

•	andards for mixture					-	
Component		Breathing Zone ppm Breathing Zone mg/m ³					
Personal Pro	tection						
Eye:	Safety ey any paint	afety eyewear with splash guards or side shields to prevent eye contact is recommended when using ny paint.					
Hands/Feet		Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet ecommended.					
Other	Overalls,	alls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.					
		good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of naterials. Wash hands thoroughly before handling food.					
Respirator	None req		0,	0			
SECTION	9.	PHYSICAL A	AND CHEMIC	CAL PROP	ERTIES		
Appearance	Clear liqui	d					
Odour	pH V	apour Pressure	Vapour Density	Boiling Point	Melt Freeze	Solubility	Volatile by Weigh
Hydrocarbon	n/a		>1	82°C		Immiscible 100	
SECTION	10.	STABILITY	AND ACTIV	ITY			

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Materials

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

RALI MULTIPURPOSE REDUCER

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component

Oral:LD50 mg/k Dermal:LD50 mg/k

Inhale:LC50 pp

SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment No data available for this product

Component

Fish:LC50 mg/Lt

BCF:<100 Kow

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number	1263
Proper Shipping Name	Paint related product
Subsidiary Risk	
Poison Schedule	
Packing Group:	II
Class	3
HAZCHEM Code	3[Y]E
Special precautions for u	Iser

SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants - Flammable

Approved Handler Class 3.1B required for quantities greater than 250Lt (containers greater than 5Lt capacity) or greater than 500Lt (containers less than 5Lt capacity)

SECTION 16.	OTHER INFORMATION
Date of Preparation	9/07/2012
Literature references	MSDS's for individual raw material
Abbreviations:	
NOHSC	National Occupational Health and Safety
TWA	Time weighted average
STEL	Short term exposure limit
CAS Number	Chemical Abstract Service registry numb
TLV	Threshold limit value
Marine Pollutant	Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.