SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: RALI TRUCK KLEEN

Other Names: Formerly Break

Recommended Use: Soil release agent

Company Name: Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND

P O Box 38242, Wellington Mail Centre

Phone: (04) 577 0500 Fax: (04) 577 0600

1800 738 38

Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214

P O Box 924, Beenleigh, Queensland 4207

AUSTRALIA

Emergency Telephone:

Phone

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

Australian Poisons Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Not Regulated under NZS5433 for land transportation

Risk Phrases Not assigned
Safety Phrases Not assigned
Substance Classification 6.3B 6.4A

Hazard Statements Causes skin irritation

Causes eye irritation

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENT

% CAS No TWA Ingredients Potassium tetrapolyphosphate 1-10 7320-34-5 None Establish NZ OSH (WES) 2002 2-Butoxyethanol 1-10 111-76-2 121 mg/m³ Water >60 7732-18-5 None Establish

SECTION 4. FIRST AID MEASURES

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Rinse mouth. DO NOT induce vomiting.

Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel

unwell.

Skin Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and

plenty of soap. If skin irritation occurs get medical advice/attention.

Inhaled Provide fresh air; give oxygen or artificial respiration if breathing laboured. Get medical attention.

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified

Advice to Doctor Treat symptomatically

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

RALI TRUCK KLEEN

Page 1 of 4

Resene Paints Limited

Hazchem Code Flash Point Not calculated Not calculated

n/a

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Ventilate area, avoid breathing of vapours.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Not calculated

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Remove all ignition sources. Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities

Storage Temperatures Min 1°C Max 40°C

Incompatibilities

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure No

No exposure standards has been established for this product

standards for mixture

Component Breathing Zone ppm Breathing Zone mg/m³

Personal Protection

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using

any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet

recommended.

Other Use in well ventilated area with explosion proof equipment. When added to other components mixed

material presents hazards from all components.

Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

Respirator None required

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Yellow liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze

Alcohol 7-10 100 °C Solubility Volatile by Weight Soluble 100

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

RALI TRUCK KLEEN

Page 2 of 4

Resene Paints Limited

Conditions to Avoid Freezing, excessive heat and changes in temperature Incompatible Materials Avoid storing with strong oxidisers, acids and alkalis Hazardous decomposition product Oxides of carbon and nitrogen Hazardous reactions Hazardous polymerisation will not occur.

RALI TRUCK KLEEN Page 3 of 4 Resene Paints Limited

RALI TRUCK KLEEN

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component Oral:LD50 mg/k Dermal:LD50 mg/k Inhale:LC50 pp

SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

Component Fish:LC50 mg/Lt BCF:<100 Kow

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number

Proper Shipping Name

Subsidiary Risk

Poison Schedule

Packing Group:

Class

HAZCHEM Code

Special precautions for user

SECTION 15. REGULATORY INFORMATION

Group Standard HSR002670 Surface Coatings & Colourants - Subsidiary Hazard

Approved Handler Not required

SECTION 16. OTHER INFORMATION

Date of Preparation 31/10/10

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commission

TWA Time weighted average STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry number

TLV Threshold limit value

Marine Pollutant

Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations

RALI TRUCK KLEEN Resene Paints Limited