



**Stadox**

**Silikon-Entferner NEU**

**Silicone Remover NEW**

- **Pre-treatment agent**

**Technical  
Description:**

- Substrate pre-treatment of sanded paintwork and filled substrates

# Stadox Silicone Remover NEW

---

**Flashpoint:**

• 4 °C / 39.2 °F

---

**Specific Gravity:**

• 0.74 g/cm<sup>3</sup>

---

**VOC (2004/42/EC):**

2004/42/II B(a)(850)750

The EU limit value for this product (productcategory IIB.a) in ready to use form is max 850g/ltr. The VOC content of this product in ready for use form is max. 750 g/l.

---

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.