


Always use correct Personal Protective Equipment


SPRAYING THINNER

Description



Spraying Thinner is used for thinning Spraying Enamel, Equipment Enamel, Maintenance Primer and most air-dry enamels.

Products



Product Type: Reducer
Colour: Clear
Pot Life:
Induction Time:
Density: 0.84 kg/L
Recommended DFT:
Theoretical Coverage:

Properties



VOC: 840.05 g/L
Boiling point: 136°C
Volume Solids:
Recoat-ability:
Dry Time @ 20°C:

Health & Safety



For detailed information refer to Safety Data Sheet (SDS). Safety precautions must be strictly followed during storage, handling and use. Avoid breathing vapour. Use protective clothing and respiratory equipment. Product is flammable.

Transport & Storage



Sizes: 1L, 4L, 20L, 208L
Dangerous Goods: 3A
UN: 1263
Hazchem: 3[Y]
Packing Group: III
Shipment name: PAINT Related Material
Flash point: 27°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.