

Always use correct Personal Protective Equipment


TYRE & RADIATOR BLACK

Description



Tyre & Radiator Black is a fast drying product for use directly onto tyre's/radiator tanks and any metal surface where a quick clean-up type paint coating is required.

Products



Product Type: Copolymer Alkyd/Hydrocarbon resin

Colour: Black

Finish: Gloss

Pot Life:

Induction Time:

Density: 0.887 kg/L

Recommended DFT: 25 microns

Theoretical Coverage:

Properties



VOC: 685 g/L


Volume Solids: 21.89%

Recoat-ability:

Dry Time @ 20°C: Touch dry: 10-15 minutes

Hard dry: 4 hours

Substrates




Automotive components or any equipment where resistance to chemicals and prolonged exposure is not a prerequisite.

Surface Preparation



Ensure surface is washed with water and soap. Degreased with RALI Wax & Grease Remover and rough up with suitable abrasive if necessary.

Directions For Use



Mixing Ratio:

Thinning: Thin Radiator Black if necessary with GP Thinners

Application Method: Stir well. Radiator Black comes ready for use and is best sprayed with a conventional gun with a lacquer set up. Strain before application

Clean Up: GP Thinners


No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Always use correct Personal Protective Equipment

Spray Equipment: Compliant / Conventional Suction and Gravity feed
Tip size: 1.6 - 2.0 mm
Air pressure: 310 - 380 kPa (45-55 psi)

**Health & Safety**

For detailed information refer to Safety Data Sheet (SDS). Avoid breathing vapour. Ensure adequate ventilation. Wear protective mask if working in confined spaces. Highly flammable - keep away from sparks and naked flames. If eyes become contaminated flush with water for fifteen minutes.

Transport & Storage

Sizes: 4L, 20L
Dangerous Goods: 3A
UN: 1263
Hazchem: 3[Y]E
Packing Group: II
Shipment name: PAINT Flammable
Flash point: 4°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.