

DINITROL® 8550

Clear Lacquer Spray

Body Repair

Body Repair

Characteristics:

DINITROL 8550 Clear Lacquer Spray is an acrylic lacquer for sealing lacquered surfaces.

Application:

Also ideal for wheel rims. High-pigmented silver lacquer which may display good adhesion but are susceptible to ageing can be perfectly sealed with Clear Lacquer Spray.

Method of Use:

Clear Lacquer Spray is used for renovation work in paint workshops. The substrate must be clean and free from grease, dust and rust. Before use, shake the can (1 – 2 mins) until the mixing ball can clearly be heard. Apply the material in an even cross coat.

For small surfaces, the product can also be sprayed in a circular movement.

The product should be sprayed at a distance of 20 – 30 cm. In order to prevent any blockages, hold the can downwards after use and briefly spray pure gas.

Technical data:

Base:	Acrylic resin
Colour:	Colourless
Density:	0.798 g/ml
Flash point:	< - 19°C
Heat resistance:	> 80°C
Propellant:	Propane/butane
Drying time: Touch dry at 20°C	Approx. 25 mins / 40 µ
Storage:	Cool and dry
Storage time:	24 months
Delivery form:	400 ml spray can (standard)
Hazard indication:	Highly flammable

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Telephone:
+49 (0) 52 81 / 9 82 98-0
Fax:
+49 (0) 52 81 / 9 82 98-60
Email:
service@dinol.com