



## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: **Dinitrol 1000 Spray**  
Product Use: Anticorrosion additive  
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Auto Body Equipment**  
Address: 17 The Boulevard  
Te Rapa, Hamilton, 3200  
New Zealand

Telephone: +64 7 849 3514  
Email: office@abe.co.nz  
**Emergency No: 0800 764 766 (National Poison Centre)**

Date of SDS Preparation: 10 April 2018

### Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

**EPA Approval No: Aerosols (Flammable) – HSR002515**

#### Pictograms



Flammable Irritant Chronic Ecotoxic

Signal Word: **DANGER**

HSNO Classes	Hazard Code	Hazard Statement	GHS Category
2.1.2A	H222	Extremely Flammable aerosol	Flam. Aerosol. 1
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.8B	H361	Suspected of damaging fertility or the unborn child.	Repr. 2
6.9N	H336	May cause drowsiness or dizziness.	STOT SE 3
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.

Product Name: Dinitrol 1000 Spray  
Date of SDS: 10 April 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: 64 9 475 5240 www.techcomp.co.nz

P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing fumes, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective PPE as described in Section 8
P281	Use personal protective equipment as required.

Response Code	Response Statement
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

### Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated heavy	25- <55	64742-48-9
Propane Liquefied	10- <25	74-98-6
Butane, pure	10- <25	106-97-8
Calcium Sulfonate	1- <5	61789-86-4

### Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for 15 minutes. If eye irritation persists: Get medical advice.
If on Skin	Take off contaminated clothing and wash before re-use. Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. Wash out mouth thoroughly with water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Call a POISON CENTER if unwell.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

#### Most important symptoms and effects, both acute and delayed

Symptoms:

**Ingestion:** Not applicable.

Product Name: Dinitrol 1000 Spray  
Date of SDS: 10 April 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: 64 9 475 5240 www.techcomp.co.nz

<b>Inhalation:</b>	Not applicable.
<b>Skin:</b>	Causes skin irritation and may cause an allergic reaction.
<b>Eye:</b>	Not applicable.
<b>Chronic:</b>	Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.

## Section 5. Fire Fighting Measures

<b>Hazard Type</b>	Flammable Aerosol
<b>Hazards from decomposition products</b>	Carbon monoxide.
<b>Suitable Extinguishing media</b>	CO2, sand, extinguishing powder. Do not use water with full jet.
<b>Precautions for firefighters and special protective clothing</b>	Protective equipment: Mount respiratory protective device. Cool endangered receptacles with water spray.
<b>HAZCHEM CODE</b>	<b>2YE</b>

## Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel. Ensure adequate ventilation. Keep away from ignition sources.

Do not allow product to reach sewage system or any water course.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents.

Dispose of waste according to the applicable local and national regulations.

## Section 7. Handling and Storage

### Precautions for Handling:

- Keep out of reach of children.
- Read label before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Do not spray on an open flame or other ignition source.
- Pressurized container: Do not pierce or burn, even after use.
- Avoid breathing fumes, vapours or spray.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Open and handle receptacle with care.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective PPE as described in Section 8
- Use personal protective equipment as required.

### Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C.
- Do not seal receptacle gas tight.

**WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance	TWA		STEL	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Propane [74-98-6]	Simple asphyxiant – may present an explosion hazard			
Butane [106-97-8]	800	1,900	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

DNELs		
<b>64742-48-9 Naphtha (petroleum), hydrotreated heavy</b>		
Oral	Acute - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Acute - systemic effects, general population	125 mg/kg (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalation	Acute - systemic effects, general population	900 mg/m <sup>3</sup> (General Population)
	Long-term - systemic effects, worker	871 mg/m <sup>3</sup> (Worker)
<b>106-97-8 Butane, pure</b>		
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	

**Engineering Controls**

Ensure there is adequate ventilation available.

**Personal Protection Equipment**

<b>Eyes</b>	Tightly sealed goggles with side shields.
<b>Hands</b>	Material of gloves: Nitrile rubber Penetration time of glove material > 480 min. Recommended thickness of the material: 0.12mm
<b>Skin</b>	Body protection: Protective work clothing
<b>Respiratory</b>	Filter AX
<b>General</b>	Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin.

**Section 9****Physical and Chemical Properties**

<b>Form</b>	Aerosol
<b>Colour</b>	Light Brown
<b>Odour</b>	Solvent like
<b>Odour Threshold</b>	Not available
<b>pH</b>	Not available
<b>Boiling Point</b>	-44°C

<b>Melting Point</b>	Not available
<b>Freezing Point</b>	Not available
<b>Flash Point</b>	<-20 °C (DIN 53213)
<b>Flammability</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Upper and Lower Explosive Limits</b>	0.6% - 10.9% (vol)
<b>Vapour Pressure @20°C</b>	8300 hPa
<b>Density@ 20°C</b>	0.71 g/cm <sup>3</sup> (DIN 51757)
<b>Specific Gravity</b>	Not available
<b>Water Solubility</b>	Not miscible or difficult to mix.
<b>Partition Coefficient:</b>	Not available
<b>Ignition Temperature</b>	Product is not self-igniting.
<b>Decomposition Temperature</b>	Not available
<b>Kinematic Viscosity @20°C</b>	Not available
<b>Particle Characteristics</b>	Not available
<b>Solvent content</b>	Organic Solvents: 66.3%
<b>Solids content</b>	33.7 % (DIN 53216)
<b>VOC(EU)</b>	66.31%
<b>VOC(EU)</b>	470.8g/L
<b>VOCV</b>	66.31%

### Section 10. Stability and Reactivity

<b>Stability of Substance</b>	This product is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reactions known.
<b>Conditions to Avoid</b>	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
<b>Incompatible Materials</b>	Combustible materials, oxidising agents.
<b>Hazardous Decomposition Products</b>	Carbon monoxide.

### Section 11 Toxicological Information

#### Acute Effects:

<b>Swallowed</b>	Not applicable.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	May cause drowsiness or dizziness.
<b>Eye</b>	Not applicable.
<b>Skin</b>	Causes skin irritation. May cause an allergic skin reaction.

#### Chronic Effects:

<b>Carcinogenicity</b>	Not applicable.
<b>Reproductive Toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	Not applicable.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Not applicable.

**Acute Toxicity -**

Chemical Name	LD50 (Oral)	LD50 (Dermal)	LC50 (inhalation)
<b>Product</b>			
64742-48-9 Naphtha (petroleum), hydrotreated	>5000mg/kg(Rat)	>3000mg/kg(Rat)	
106-97-8 Butane, pure			658mg/l 4h (Rat)

**Section 12. Ecotoxicological Information**

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

<b>Persistence and degradability</b>	No data available
<b>Bioaccumulation</b>	No data available
<b>Mobility in Soil</b>	No data available
<b>Other adverse effects</b>	Slightly hazardous for water. Do not allow undiluted product to reach ground water, water course or sewage system.

Do not allow to enter waterways.

**Section 13. Disposal Considerations****Disposal Method:**

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – Flammable Aerosol, Ecotoxic" and that the label also has the Flammable, Ecotoxic Pictograms, waste type identifier, and the business name, address, and phone number.

**Precautions or methods to avoid:** Avoid release to the environment.

**Section 14 Transport Information**

**This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012**

**Road and Rail Transport**

UN No: 1950  
Class-primary 2  
Proper Shipping Name: AEROSOLS

**Air Transport**

UN No: 1950  
Class-primary 2  
Proper Shipping Name: AEROSOLS

**Marine Transport**

UN No: 1950  
Class-primary 2  
Proper Shipping Name: AEROSOLS

**Section 15****Regulatory Information****New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Aerosols (Flammable) – HSR002515

HSNO Classification: 2.1.2A, 6.3A, 6.5B, 6.8B, 6.9N, 9.1B

<b>HSW (HS) Regulations 2017 and EPA Notices</b>	<b>Trigger Quantity</b>
Certified Handler	Not required
Location Certificate	3000L (AWC)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L (9.1B)
Emergency Response Plan	1000L (9.1B)
Secondary Containment	1000L (9.1B)
Fire Extinguishers	>3000(AWC) (require 1x )
Restriction of Use	Only use for the intended purpose.

**Section 16****Other Information****Glossary**

EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

**References:**

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

**Disclaimer**

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Auto Body Equipment, if further information is required.

Issue Date:

10 April 2018

Review Date:

10 April 2023