



# **Standoflex**

## **Plastik-Primer U3060**

## **Plastic Primer U3060**

- **1K Primer for 3-stage plastic painting**
- **Easy to use**
- **Adheres to all exterior plastic car parts**
- **Ready to spray**



### **Technical Description:**

- 1 spray pass Standoflex Plastic Primer U3060
- Flash off 10 min / 18-22°C
- Overcoat wet-on-wet with plasticised Standox Filler

# Standoflex Plastik-Primer U3060

## Substrate:

- Exterior plastic car parts

## Application:

Ready to spray

Shake well before use



Compliant 1.3 - 1.4 mm  
2.0 - 2.5 bar inlet pressure  
1 = 1 - 2 micron


## Pretreatment / Cleaning:



For substrate preparation information see Standox Painting System S1.



HVLP 1.4 - 1.5 mm  
0.7 bar atomization pressure  
1 = 1 - 2 micron



Air dry 10 min / 18-22°C



This product is classified according to regulation (EC) 1272/2008 (CLP).

Please consult the Safety Data Sheet.  
It is strongly recommended to use appropriate personal protection equipment during application.



Plasticised Standox Filler

# Standoflex Plastik-Primer U3060

---

**Flashpoint:**

- 23 °C / 73.4 °F
- 

**Specific Gravity:**

- 0.88 g/cm<sup>3</sup>
- 

**Solid Content****(without thinner added):**

- 4.8 Weight %
  - 3.8 Volume %
- 

**Theoretical****Coverage:**

17 m<sup>2</sup>/l at 2 micron dry film thickness

---

**Cleaning of equipment:**

Clean after use with Standox Cleaning Thinner.

---

**Important remarks:**

- Apply a thin coat of Standoflex Plastic Primer U3060
- See Standox Plastic Painting Systems (S7.0 - 7.8)

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.