

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
Product code: 4024669500684  
Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 1- 7

## 1. Identification of the substance/mixture and of the company/undertaking

|  |  |
|--|--|
| <b>Product name</b>                              | STANDOBLUE BASECOAT<br>MIX 168<br>MAGENTA  |
| <b>Product code</b>                              | 4024669500684  |
| <b>Intended use of the substance/preparation</b> | Intermediate   |
| <b>Supplier</b>                                  | Axalta Coating Systems Australia Pty Limited                                       |
| Street address                                   | 15 - 23 Melbourne Road, Riverstone NSW 2765, Australia                             |
| Telephone  |  |
| Telefax  |  |
| <b>Emergency Information</b>                     |  |
| Emergency telephone number                       | +(64) 9801 0034<br>NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248 |
| Importer   | Resene Automotive & Light Industrial   |
| Street/Box                                       | 4 Te Apunga Place, Mt Wellington,<br>Auckland, NZ                                  |
| Nat.-Code/Postal code/City                       |  |
| Telephone  | +64 (09) 259 2738  |
| Date of preparation                              | 2017-07-04   |

## 2. Hazards identification

Not classified as a Dangerous Good under NZS 5433  
Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

### HSNO Classification

Flammable liquids Category 3.1D

### GHS-Labeling

Hazard symbols

Not classified according to GHS criteria

Signal word: Warning

Hazard statements

Combustible liquid.

Precautionary statements

Keep away from open flames/hot surfaces. - No smoking.  
Store in a well-ventilated place. Keep cool.

### Other hazards which do not result in classification

Safety data sheet available for professional user on request.

## 3. Composition/information on ingredients

### Pure substance/mixture

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
 Product code: 4024669500684  
 Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 2- 7

Mixture

#### Hazardous components

| CAS-No.    | Chemical name                   | Concentration | GHS Hazardous |
|------------|---------------------------------|---------------|---------------|
| 34590-94-8 | (2-methoxymethylethoxy)propanol | 1 - 3%        |               |
| 67-63-0    | propan-2-ol                     | 0.3 - 1.0%    | ✓             |
| 1332-58-7  | Kaolin                          | 0.3 - 1.0%    |               |
| 108-01-0   | 2-dimethylaminoethanol          | 0.3 - 1.0%    | ✓             |
| 57-55-6    | Propane-1,2-diol                | 0.3 - 1.0%    |               |
| 67-64-1    | acetone                         | 0.1 - 0.3%    | ✓             |
| 78-93-3    | butanone                        | 0.1 - 0.3%    | ✓             |

Non-regulated ingredients 90 - 100%

## 4. First aid measures

#### Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

#### Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

#### Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

#### Ingestion

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

#### Most Important Symptoms/effects, acute and delayed

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

#### Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. Firefighting measures

#### Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical, Water spray.

#### Extinguishing media which shall not be used for safety reasons

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
 Product code: 4024669500684  
 Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 3- 7

High volume water jet

#### Specific hazards

Combustible liquid. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

#### Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray.

## 6. Accidental release measures

#### Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

#### Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

#### Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

## 7. Handling and storage

#### Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

#### Storage

#### Suitable storage conditions

Observe label precautions. Storage temperature: +5 to +35°C. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

## 8. Exposure controls/personal protection

#### National occupational exposure limits

| Chemical name                   |      |                         |
|---------------------------------|------|-------------------------|
| (2-methoxymethylethoxy)propanol | TWA  | 100 ppm                 |
|                                 | TWA  | 606 mg/m <sup>3</sup>   |
|                                 | STEL | 150 ppm                 |
|                                 | STEL | 909 mg/m <sup>3</sup>   |
| propan-2-ol                     | TWA  | 400 ppm                 |
|                                 | TWA  | 983 mg/m <sup>3</sup>   |
|                                 | STEL | 500 ppm                 |
|                                 | STEL | 1,230 mg/m <sup>3</sup> |
| Kaolin                          | TWA  | 2 mg/m <sup>3</sup>     |

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
 Product code: 4024669500684  
 Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 4- 7

| Chemical name          |      |                         |
|------------------------|------|-------------------------|
| 2-dimethylaminoethanol | TWA  | 2 ppm                   |
|                        | TWA  | 7.4 mg/m <sup>3</sup>   |
|                        | STEL | 6 ppm                   |
|                        | STEL | 22 mg/m <sup>3</sup>    |
| Propane-1,2-diol       | TWA  | 10 mg/m <sup>3</sup>    |
| acetone                | TWA  | 500 ppm                 |
|                        | TWA  | 1,185 mg/m <sup>3</sup> |
|                        | STEL | 1,000 ppm               |
|                        | STEL | 2,375 mg/m <sup>3</sup> |
| butanone               | TWA  | 150 ppm                 |
|                        | TWA  | 445 mg/m <sup>3</sup>   |
|                        | STEL | 300 ppm                 |
|                        | STEL | 890 mg/m <sup>3</sup>   |

### Engineering measures

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Glossary

CEIL Ceiling exposure limit  
 STEL Short term exposure limit  
 TWA Time weighted average

### Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

### Eye protection

Use safety eyewear designed to protect against splash of products.

### Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

| Chemical name | Glove material         | Glove thickness | Break through time |
|---------------|------------------------|-----------------|--------------------|
| butanone      | Viton (R) <sup>®</sup> | 0.7 mm          | 10 MIN             |

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril <sup>®</sup> glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

### Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

### Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

## 9. Physical and chemical properties

### Appearance

**Form** : liquid      **Colour**: red      **Odor Threshold** : No data available

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
 Product code: 4024669500684  
 Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 5- 7

|  |   |
|--|---|
| pH                                     | No data available.                        |
| Freezing point                         | Not applicable.                           |
| Boiling point                          | 100 °C                                    |
| Flash point                            | 80 °C EN ISO 3679                         |
| Evaporation rate                       | Slower than Ether                         |
| Flammability                           |   |
| Upper explosion limit                  | Not applicable.                           |
| Lower explosion limit                  | Not applicable.                           |
| Vapour pressure                        | 0.6 hPa                                   |
| Solubility(ies)                        | appreciable                               |
| Vapour density                         | No data available                         |
| Density                                | 1.03 g/cm <sup>3</sup> DIN 53217/ISO 2811 |
| Partition coefficient: n-octanol/water | No data available                         |
| Ignition temperature                   | 501 °C DIN 51794                          |
| Decomposition temperature              |   |
| Viscosity (23 °C)                      | <20 s ISO 2431-1993 6 mm                  |

Does not sustain combustion.

## 10. Stability and reactivity

### Stability

Stable

### Hazardous polymerisation

Will not occur.

### Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### Information on likely routes of exposure

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

not hazardous

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
Product code: 4024669500684  
Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 6- 7

**Acute dermal toxicity**

not hazardous

**Acute inhalation toxicity**

not hazardous

% of unknown composition: 0 %

**Skin corrosion/irritation**

Not classified according to GHS criteria

**Serious eye damage/eye irritation**

Not classified according to GHS criteria

**Respiratory sensitisation**

Not classified according to GHS criteria

**Skin sensitisation**

Not classified according to GHS criteria

**Germ cell mutagenicity**

Not classified according to GHS criteria

**Carcinogenicity**

Not classified according to GHS criteria

**Toxicity for reproduction**

Not classified according to GHS criteria

**Target Organ Systemic Toxicant - Single exposure**

Not classified according to GHS criteria

**Target Organ Systemic Toxicant - Repeated exposure**

Not classified according to GHS criteria

**Aspiration toxicity**

Not classified according to GHS criteria

**Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )**

No information available.

**Symptoms related to the physical, chemical and toxicological characteristics**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## 12. Ecological information

Product does not contain any environmentally hazardous substances and product is not classified per GHS

**Ecotoxicity effects**

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in soil**

No information available.

Product name: STANDOBLUE BASECOAT MIX 168 MAGENTA  
Product code: 4024669500684  
Print Date: 2017-07-04 v1.0 Revision Date: 2017-07-04

NZ/en Page 7- 7

**Other adverse effects**

No information available.

## 13. DISPOSAL CONSIDERATIONS

**Waste disposal methods**

Dispose of in accordance with local regulations.

**Disposal considerations**

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

## 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

**Matters needing attention for transportation**

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

## 15. Regulatory information

**National regulatory information**

HSNO Approval Code HSR002657  
HSNO Classification  
Flammable liquids Category 3.1D

## 16. Other information

Revision Note

Version Changes

1.0

Revision Date: 2017-07-04  
B11969188

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet