

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 1- 9

1. Identification of the substance/mixture and of the company/undertaking

Product name STANDOCRYL VOC
MIX 416
SIGNAL BLUE

Product code 4024669684162

Intended use of the substance/preparation

Coating for professional use

Supplier Axalta Coating Systems Australia Pty Limited
Street address 15 - 23 Melbourne Road, Riverstone NSW 2765, Australia
Telephone
Telefax

Emergency Information

Emergency telephone number +(64) 9801 0034
NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248

Importer Resene Automotive & Light Industrial
Street/Box 4 Te Apunga Place, Mt Wellington, Auckland, NZ

Nat.-Code/Postal code/City
Telephone +64 (09) 259 2738

Date of preparation 2017-07-04

2. Hazards identification

Classified as a Dangerous Good according to NZS 5433

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

HSNO Classification

| | |
|---------------------------|---------------|
| Flammable liquids | Category 3.1C |
| Skin corrosion/irritation | Category 6.3B |
| Skin sensitisation | Category 6.5B |
| Acute aquatic toxicity | Category 9.1C |
| Chronic aquatic toxicity | Category 9.1C |

GHS-Labeling

Hazard symbols



Signal word: Warning

Hazard statements

Flammable liquid and vapour.
Causes mild skin irritation.
May cause an allergic skin reaction.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Avoid breathing dust/ vapours/ spray.
Avoid release to the environment.

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 2- 9

Wear protective gloves/protective clothing/eye protection/face protection.
 If skin irritation or rash occurs: Get medical advice/ attention.
 Wash contaminated clothing before reuse.
 Store in a well-ventilated place. Keep cool.

Other hazards which do not result in classification

Contains epoxy constituents. See information supplied by the manufacturer. Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; 2,3-epoxypropyl neodecanoate; methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

3. Composition/information on ingredients**Pure substance/mixture**

Mixture

Hazardous components

| CAS-No. | Chemical name | Concentration | GHS Hazardous |
|------------|----------------------------------------------------------|---------------|---------------|
| 123-86-4 | n-butyl acetate | 20 - 30% | ✓ |
| 64742-95-6 | solvent naphtha (petroleum), light arom. (<0,1% benzene) | 3 - 5% | ✓ |
| 95-63-6 | 1,2,4-trimethylbenzene | 1 - 3% | ✓ |
| 110-12-3 | 5-methylhexan-2-one | 1 - 3% | ✓ |
| 108-67-8 | mesitylene | 0.3 - 1.0% | ✓ |
| 64-19-7 | acetic acid | 0.3 - 1.0% | ✓ |
| 41556-26-7 | bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | 0.3 - 1.0% | ✓ |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 0.3 - 1.0% | ✓ |
| 26761-45-5 | 2,3-epoxypropyl neodecanoate | 0.3 - 1.0% | ✓ |
| 628-63-7 | pentyl acetate | 0.3 - 1.0% | ✓ |
| 61788-46-3 | Amines, coco alkyl | 0.1 - 0.3% | ✓ |
| 98-82-8 | cumene | 0.1 - 0.3% | ✓ |
| 82919-37-7 | methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 0.1 - 0.3% | ✓ |
| 78-93-3 | butanone | 0.1 - 0.3% | ✓ |
| 1330-20-7 | xylene | 0.1 - 0.3% | ✓ |

Non-regulated ingredients 60 - 70%

4. First aid measures**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 3- 9

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. If this product is mixed with an isocyanate, skin contact may cause sensitization.

Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons

High volume water jet

Specific hazards

Flammable liquid and vapour. Vapours may form explosive mixtures with air. Remove all sources of ignition. Solvent vapours are heavier than air and may spread along floors. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. Handling and storage

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 4- 9

Handling

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

Storage

Suitable storage conditions

Observe label precautions. Refer to Technical Data Sheet (TDS) for further information about storage temperature. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

8. Exposure controls/personal protection

National occupational exposure limits

| Chemical name | | |
|------------------------|------|-----------------------|
| n-butyl acetate | TWA | 150 ppm |
| | TWA | 713 mg/m ³ |
| | STEL | 200 ppm |
| | STEL | 950 mg/m ³ |
| 1,2,4-trimethylbenzene | TWA | 25 ppm |
| | TWA | 123 mg/m ³ |
| 5-methylhexan-2-one | TWA | 50 ppm |
| | TWA | 234 mg/m ³ |
| mesitylene | TWA | 25 ppm |
| | TWA | 25 ppm |
| | TWA | 123 mg/m ³ |
| | TWA | 123 mg/m ³ |
| acetic acid | TWA | 10 ppm |
| | TWA | 25 mg/m ³ |
| | STEL | 15 ppm |
| | STEL | 37 mg/m ³ |
| pentyl acetate | TWA | 100 ppm |
| | TWA | 532 mg/m ³ |
| cumene | TWA | 25 ppm |
| | TWA | 125 mg/m ³ |
| | STEL | 75 ppm |
| | STEL | 375 mg/m ³ |
| butanone | TWA | 150 ppm |
| | TWA | 445 mg/m ³ |
| | STEL | 300 ppm |
| | STEL | 890 mg/m ³ |
| xylene | TWA | 50 ppm |
| | TWA | 217 mg/m ³ |

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 5- 9

Engineering measures

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Glossary

CEIL Ceiling exposure limit
 STEL Short term exposure limit
 TWA Time weighted average

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Eye protection

Use safety eyewear designed to protect against splash of products.

Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

| Chemical name | Glove material | Glove thickness | Break through time |
|----------------------------------------------------------|----------------|-----------------|--------------------|
| n-butyl acetate | Viton (R) ® | 0.7 mm | 10 MIN |
| | Nitrile rubber | 0.33 mm | 30 MIN |
| solvent naphtha (petroleum), light arom. (<0,1% benzene) | Viton (R) ® | 0.7 mm | 30 MIN |
| butanone | Viton (R) ® | 0.7 mm | 10 MIN |
| xylene | Nitrile rubber | 0.33 mm | 30 MIN |
| | Viton (R) ® | 0.7 mm | 480 MIN |

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

9. Physical and chemical properties**Appearance**

Form : liquid **Colour**: blue **Odor Threshold** : No data available

| | |
|------------------|-------------------|
| pH | Not applicable |
| Freezing point | Not applicable. |
| Boiling point | 125 °C |
| Flash point | 25 °C |
| Evaporation rate | Slower than Ether |
| Flammability | |

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 6- 9

| | | |
|----------------------------------------|------------------------|--------------------|
| Upper explosion limit | 7.5 % | |
| Lower explosion limit | 0.7 % | |
| Vapour pressure | 4.9 hPa | |
| Solubility(ies) | moderate | |
| Vapour density | No data available | |
| Density | 1.02 g/cm ³ | DIN 53217/ISO 2811 |
| Partition coefficient: n-octanol/water | No data available | |
| Ignition temperature | 415 °C | DIN 51794 |
| Decomposition temperature | | |
| Viscosity (23 °C) | 28 s | ISO 2431-1993 6 mm |

10. Stability and reactivity

Stability

Stable

Hazardous polymerisation

Will not occur.

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

not hazardous

Acute dermal toxicity

not hazardous

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 7- 9

Acute inhalation toxicity

not hazardous

% of unknown composition: 0 %

Skin corrosion/irritation

| | |
|----------------------------------------------------------|-------------|
| n-butyl acetate | Category 3 |
| solvent naphtha (petroleum), light arom. (<0,1% benzene) | Category 3 |
| 1,2,4-trimethylbenzene | Category 2 |
| 5-methylhexan-2-one | Category 3 |
| mesitylene | Category 2 |
| acetic acid | Category 1A |
| pentyl acetate | Category 3 |
| Amines, coco alkyl | Category 1A |
| butanone | Category 3 |
| xylene | Category 2 |

Serious eye damage/eye irritation

Not classified according to GHS criteria

Respiratory sensitisation

Not classified according to GHS criteria

Skin sensitisation

| | |
|---------------------------------------------------|------------|
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | Category 1 |
| 2,3-epoxypropyl neodecanoate | Category 1 |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Category 1 |

Germ cell mutagenicity

Not classified according to GHS criteria

Carcinogenicity

Not classified according to GHS criteria

Toxicity for reproduction

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Repeated exposure

Not classified according to GHS criteria

Aspiration toxicity

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitizer and an irritant. Low molecular epoxy constituents are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies. Avoid skin and eye contact. Avoid inhalation of vapour or mist.

12. Ecological information

Product contains environmentally hazardous substances and product is not classified per GHS.

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 8- 9

Ecotoxicity effects

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

Acute aquatic toxicity

| | |
|---------------------------------------------------|------------|
| n-butyl acetate | Category 3 |
| 1,2,4-trimethylbenzene | Category 2 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | Category 1 |
| Amines, coco alkyl | Category 1 |
| cumene | Category 2 |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Category 1 |

Chronic aquatic toxicity

| | |
|----------------------------------------------------------|------------|
| solvent naphtha (petroleum), light arom. (<0,1% benzene) | Category 2 |
| 1,2,4-trimethylbenzene | Category 2 |
| mesitylene | Category 2 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | Category 1 |
| 2,3-epoxypropyl neodecanoate | Category 2 |
| Amines, coco alkyl | Category 1 |
| cumene | Category 2 |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Category 1 |

% of unknown composition 0%

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in soil

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste disposal methods**

Dispose of in accordance with local regulations.

Disposal considerations

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

14. Transport information**NZS5433**

Proper shipping name: PAINT

UN number: 1263

Hazard Class: 3

Packing group: III

Hazchem Code: 3Y

IMDG (Sea transport)

Proper shipping name: PAINT

Product name: STANDOCRYL VOC MIX 416 SIGNAL BLUE

Product code: 4024669684162

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 9- 9

UN number: 1263
Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: III
Marine Pollutant: no
EmS: F-E,S-E

ICAO/IATA (Air transport)

Proper shipping name: PAINT

UN number: 1263
Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: III

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

National regulatory information

HSNO Approval Code HSR002662

HSNO Classification

Skin corrosion/irritation Category 6.3B

Skin sensitisation Category 6.5B

Flammable liquids Category 3.1C

Acute aquatic toxicity Category 9.1C

Chronic aquatic toxicity Category 9.1C

16. Other information

Revision Note

| Version | Changes |
|---------|---------|
| 1.0 | |

Revision Date: 2017-07-04

B12253766

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet