

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 1- 7

## 1. Identification of the substance/mixture and of the company/undertaking

<b>Product name</b>	STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE
<b>Product code</b>	4024669863192
<b>Intended use of the substance/preparation</b>	Coating for professional use
<b>Supplier</b>	Axalta Coating Systems Australia Pty Limited
Street address	15 - 23 Melbourne Road, Riverstone NSW 2765, Australia
Telephone	
Telefax	
<b>Emergency Information</b>	
Emergency telephone number	+(64) 9801 0034 NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248
Importer	Resene Automotive & Light Industrial
Street/Box	4 Te Apunga Place, Mt Wellington, Auckland, NZ
Nat.-Code/Postal code/City	
Telephone	+64 (09) 259 2738
Date of preparation	2017-07-04

## 2. Hazards identification

Not classified as a Dangerous Good under NZS 5433

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

### HSNO Classification

Flammable liquids	Category 3.1D
Skin corrosion/irritation	Category 6.3B
Serious eye damage/eye irritation	Category 8.3A

### GHS-Labeling

Hazard symbols



Signal word: Danger

Hazard statements

Combustible liquid.  
Causes mild skin irritation.  
Causes serious eye damage.

Precautionary statements

Keep away from open flames/hot surfaces. - No smoking.  
Wear eye protection/ face protection.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER/doctor.  
Store in a well-ventilated place. Keep cool.

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 2- 7

**Other hazards which do not result in classification**

None known.

### 3. Composition/information on ingredients

**Pure substance/mixture**

Mixture

**Hazardous components**

CAS-No.	Chemical name	Concentration	GHS Hazardous
71-41-0	pentan-1-ol	5 - 10%	✓
67-64-1	acetone	1 - 3%	✓
108-01-0	2-dimethylaminoethanol	0.1 - 0.3%	✓
121-44-8	triethylamine	0.1 - 0.3%	✓

Non-regulated ingredients 90 - 100%

### 4. First aid measures

**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

**Skin contact**

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

**Inhalation**

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

**Ingestion**

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

**Most Important Symptoms/effects, acute and delayed****Inhalation**

May cause nose and throat irritation. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

**Ingestion**

May result in gastrointestinal distress.

**Skin or eye contact**

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. If this product is mixed with an isocyanate, skin contact may cause sensitization.

**Notes to physician**

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

### 5. Firefighting measures

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 3- 7

**Suitable extinguishing media**

Water spray, Dry chemical, Foam

**Extinguishing media which shall not be used for safety reasons**

High volume water jet

**Specific hazards**

Combustible liquid. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

**Special Protective Equipment and Fire Fighting Procedures**

Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray.

## 6. Accidental release measures

**Personal precautions**

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

**Environmental precautions**

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

**Methods for cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

## 7. Handling and storage

**Safe handling advice**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

**Storage****Suitable storage conditions**

Observe label precautions. Storage temperature: +5 to +35°C. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**Suitable container and packaging materials for safe storage**

Always keep in containers made of the same material as the supply container.

## 8. Exposure controls/personal protection

**National occupational exposure limits**

Chemical name		
acetone	TWA	500 ppm
	TWA	1,185 mg/m <sup>3</sup>
	STEL	1,000 ppm
	STEL	2,375 mg/m <sup>3</sup>
2-dimethylaminoethanol	TWA	2 ppm
	TWA	7.4 mg/m <sup>3</sup>
	STEL	6 ppm
	STEL	22 mg/m <sup>3</sup>

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 4- 7

## Chemical name

triethylamine	TWA	3 ppm
	TWA	12 mg/m <sup>3</sup>
	STEL	5 ppm
	STEL	20 mg/m <sup>3</sup>

**Engineering measures**

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**Glossary**

CEIL	Ceiling exposure limit
STEL	Short term exposure limit
TWA	Time weighted average

**Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Eye protection**

Use safety eyewear designed to protect against splash of products.

**Hand protection**

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical name	Glove material	Glove thickness	Break through time
	Nitrile rubber	0.33 mm	60 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

**Skin and body protection**

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

**Hygiene measures**

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

## 9. Physical and chemical properties

**Appearance**

**Form** : liquid      **Colour**: milky      **Odor Threshold** : No data available

pH	7.5 – 9
Freezing point	Not applicable.
Boiling point	100 °C
Flash point	69 °C
Evaporation rate	Slower than Ether
Flammability	
Upper explosion limit	10 % based on organic solvents
Lower explosion limit	1.4 % based on organic solvents
Vapour pressure	3.2 hPa

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 5- 7

Solubility(ies)	appreciable	
Vapour density	No data available	
Density	1.01 g/cm <sup>3</sup>	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	No data available	
Ignition temperature	300 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	<20 s	ISO 2431-1993 6 mm

Does not sustain combustion.

## 10. Stability and reactivity

### Stability

Stable

### Hazardous polymerisation

Will not occur.

### Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### Information on likely routes of exposure

#### Inhalation

May cause nose and throat irritation. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

not hazardous

#### Acute dermal toxicity

not hazardous

#### Acute inhalation toxicity

not hazardous

% of unknown composition: 0 %

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 6- 7

**Skin corrosion/irritation**

pentan-1-ol	Category 2
acetone	Category 3
2-dimethylaminoethanol	Category 1B
triethylamine	Category 1A

**Serious eye damage/eye irritation**

pentan-1-ol	Category 1
acetone	Category 2A

**Respiratory sensitisation**

Not classified according to GHS criteria

**Skin sensitisation**

Not classified according to GHS criteria

**Germ cell mutagenicity**

Not classified according to GHS criteria

**Carcinogenicity**

Not classified according to GHS criteria

**Toxicity for reproduction**

Not classified according to GHS criteria

**Target Organ Systemic Toxicant - Single exposure**

Not classified according to GHS criteria

**Target Organ Systemic Toxicant - Repeated exposure**

Not classified according to GHS criteria

**Aspiration toxicity**

Not classified according to GHS criteria

**Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )**

No information available.

**Symptoms related to the physical, chemical and toxicological characteristics**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbition, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## 12. Ecological information

Product does not contain any environmentally hazardous substances and product is not classified per GHS

**Ecotoxicity effects**

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in soil**

No information available.

---

Product name: STANDOBLUE BASECOAT MIX 190 SPECIAL ADDITIVE

Product code: 4024669863192

Print Date: 2017-07-04

v1.0

Revision Date: 2017-07-04

NZ/en Page 7- 7

---

**Other adverse effects**

No information available.

## 13. DISPOSAL CONSIDERATIONS

**Waste disposal methods**

Dispose of in accordance with local regulations.

**Disposal considerations**

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

## 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

**Matters needing attention for transportation**

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

## 15. Regulatory information

**National regulatory information**

HSNO Approval Code	HSR002657
HSNO Classification	
Skin corrosion/irritation	Category 6.3B
Serious eye damage/eye irritation	Category 8.3A
Flammable liquids	Category 3.1D

## 16. Other information

Revision Note

Version	Changes
---------	---------

1.0	
-----	--

Revision Date: 2017-07-04

B11812739

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet