

# SAFETY DATA SHEET



Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 1- 8

## 1. Identification of the substance/mixture and of the company/undertaking

**Product name** ET755A A20LT SLOW THINNER

**Product code** 9314042010615

### Intended use of the substance/preparation

Solvent for professional use

### Supplier

Axalta Coating Systems Australia Pty Limited  
Street address 15 - 23 Melbourne Road, Riverstone NSW 2765, Australia  
Telephone  
Telefax

### Emergency Information

Emergency telephone number +(64) 9801 0034  
NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248

Importer Resene Automotive & Light Industrial

Street/Box 4 Te Apunga Place, Mt Wellington, Auckland, NZ

Nat.-Code/Postal code/City  
Telephone +64 (09) 259 2738

Date of preparation 2017-08-15

## 2. Hazards identification

Classified as a Dangerous Good according to NZS 5433

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

### HSNO Classification

Flammable liquids	Category 3.1C
Acute oral toxicity	Category 6.1D
Acute dermal toxicity	Category 6.1E
Acute inhalation toxicity	Category 6.1D
Skin corrosion/irritation	Category 6.3A
Serious eye damage/eye irritation	Category 6.4A
Carcinogenicity	Category 6.7B
Target Organ Systemic Toxicant - Repeated exposure	Category 6.9B
Acute aquatic toxicity	Category 9.1C
Chronic aquatic toxicity	Category 9.1C

### GHS-Labeling

Hazard symbols



Signal word: Warning

Hazard statements

Flammable liquid and vapour.  
Harmful if swallowed or if inhaled  
May be harmful in contact with skin.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET



Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 2- 8

## Precautionary statements

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Store in a well-ventilated place. Keep cool.

## Other hazards which do not result in classification

None known.

## 3. Composition/information on ingredients

### Pure substance/mixture

Mixture

### Hazardous components

CAS-No.	Chemical name	Concentration	GHS Hazardous
112-07-2	2-butoxyethyl acetate	50 - 60%	✓
1330-20-7	xylene	10 - 20%	✓
123-86-4	n-butyl acetate	5 - 10%	✓
98516-30-4	ethoxypropyl acetate	5 - 10%	✓
95-63-6	1,2,4-trimethylbenzene	3 - 5%	✓
64742-95-6	solvent naphtha (petroleum), light arom. (<0,1% benzene)	3 - 5%	✓
64742-94-5	Solvent naphtha (petroleum), heavy arom.	1 - 3%	✓
100-41-4	ethylbenzene	1 - 3%	✓
108-67-8	mesitylene	0.3 - 1.0%	✓
64-19-7	acetic acid	0.3 - 1.0%	✓
98-82-8	cumene	0.1 - 0.3%	✓
111-76-2	2-butoxyethanol	0.1 - 0.3%	✓
91-20-3	Naphthalene	0.1 - 0.3%	✓

Non-regulated ingredients 1 - 5%

## 4. First aid measures

### Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

### Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.



Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 3- 8

## Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

## Ingestion

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

## Most Important Symptoms/effects, acute and delayed

### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

### Ingestion

May result in gastrointestinal distress.

### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. Firefighting measures

### Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical, Water spray.

### Extinguishing media which shall not be used for safety reasons

High volume water jet

### Specific hazards

Flammable liquid and vapour. Vapours may form explosive mixtures with air. Remove all sources of ignition. Solvent vapours are heavier than air and may spread along floors. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

### Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray.

## 6. Accidental release measures

### Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

### Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

### Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

## 7. Handling and storage

### Safe handling advice

Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 4- 8

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

### Storage

#### Suitable storage conditions

Observe label precautions. Refer to Technical Data Sheet (TDS) for further information about storage temperature. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

## 8. Exposure controls/personal protection

### National occupational exposure limits

Chemical name		
xylene	TWA	50 ppm
	TWA	217 mg/m <sup>3</sup>
n-butyl acetate	TWA	150 ppm
	STEL	200 ppm
	STEL	950 mg/m <sup>3</sup>
	TWA	713 mg/m <sup>3</sup>
1,2,4-trimethylbenzene	TWA	25 ppm
	TWA	123 mg/m <sup>3</sup>
ethylbenzene	TWA	100 ppm
	STEL	125 ppm
	STEL	543 mg/m <sup>3</sup>
	TWA	434 mg/m <sup>3</sup>
mesitylene	TWA	25 ppm
	TWA	25 ppm
	TWA	123 mg/m <sup>3</sup>
	TWA	123 mg/m <sup>3</sup>
acetic acid	TWA	10 ppm
	STEL	15 ppm
	STEL	37 mg/m <sup>3</sup>
	TWA	25 mg/m <sup>3</sup>
cumene	TWA	25 ppm
	STEL	75 ppm
	STEL	375 mg/m <sup>3</sup>
	TWA	125 mg/m <sup>3</sup>
2-butoxyethanol	TWA	25 ppm
	TWA	121 mg/m <sup>3</sup>
Naphthalene	TWA	10 ppm
	STEL	15 ppm
	STEL	79 mg/m <sup>3</sup>
	TWA	52 mg/m <sup>3</sup>

### Engineering measures

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Glossary

# SAFETY DATA SHEET



Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 4- 8

CEIL Ceiling exposure limit  
STEL Short term exposure limit  
TWA Time weighted average

## Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

## Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

## Eye protection

Use safety eyewear designed to protect against splash of products.

## Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical name	Glove material	Glove thickness	Break through time
2-butoxyethyl acetate	Viton (R) ®	0.7 mm	480 m
	Nitrile rubber	0.33 mm	480 m
xylene	Nitrile rubber	0.33 mm	30 MIN
	Viton (R) ®	0.7 mm	480 MIN
n-butyl acetate	Viton (R) ®	0.7 mm	10 MIN
	Nitrile rubber	0.33 mm	30 MIN
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Viton (R) ®	0.7 mm	30 MIN
2-butoxyethanol	Viton (R) ®	0.7 mm	480 MIN
	Nitrile rubber	0.33 mm	480 MIN

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

## Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

## Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

## 9. Physical and chemical properties

### Appearance

**Form** : liquid      **Colour**: transparent      **Odor Threshold** : No data available

pH	Not applicable
Freezing point	Not applicable.
Boiling point	125 °C
Flash point	42 °C
Evaporation rate	Slower than Ether
Flammability	
Upper explosion limit	9.8 %
Lower explosion limit	0.7 %

Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 5- 8

Vapour pressure	3.6 hPa	
Solubility(ies)	moderate	
Vapour density	No data available	
Density	0.92 g/cm <sup>3</sup>	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	No data available	
Ignition temperature	325 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	>100 s	ISO 2431-1993 6 mm

## 10. Stability and reactivity

### Stability

Stable

### Hazardous polymerisation

Will not occur.

### Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### Information on likely routes of exposure

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

2-butoxyethyl acetate	Category 4
xylene	Category 5
1,2,4-trimethylbenzene	Category 5
ethylbenzene	Category 5
cumene	Category 5
2-butoxyethanol	Category 4
Naphthalene	Category 4

#### Acute dermal toxicity

2-butoxyethyl acetate	Category 4
xylene	Category 4

# SAFETY DATA SHEET



Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 6- 8

2-butoxyethanol Category 4

## Acute inhalation toxicity

2-butoxyethyl acetate Category 4  
xylene Category 4  
1,2,4-trimethylbenzene Category 4  
ethylbenzene Category 4  
2-butoxyethanol Category 4

% of unknown composition: 0 %

## Skin corrosion/irritation

xylene Category 2  
n-butyl acetate Category 3  
1,2,4-trimethylbenzene Category 2  
solvent naphtha (petroleum), light arom. (<0,1% benzene) Category 3  
Solvent naphtha (petroleum), heavy arom. Category 3  
mesitylene Category 2  
acetic acid Category 1A  
2-butoxyethanol Category 2

## Serious eye damage/eye irritation

xylene Category 2A  
1,2,4-trimethylbenzene Category 2A  
mesitylene Category 2A  
2-butoxyethanol Category 2A

## Respiratory sensitisation

Not classified according to GHS criteria

## Skin sensitisation

Not classified according to GHS criteria

## Germ cell mutagenicity

Not classified according to GHS criteria

## Carcinogenicity

Naphthalene Category 2

## Toxicity for reproduction

Not classified according to GHS criteria

## Target Organ Systemic Toxicant - Single exposure

Not classified according to GHS criteria

## Target Organ Systemic Toxicant - Repeated exposure

No data available.

## Aspiration toxicity

Not classified according to GHS criteria

## Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )

No information available.

## Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 7- 8

## 12. Ecological information

Product contains environmentally hazardous substances and product is not classified per GHS.

### Ecotoxicity effects

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

### Acute aquatic toxicity

n-butyl acetate	Category 3
1,2,4-trimethylbenzene	Category 2
ethylbenzene	Category 2
cumene	Category 2
Naphthalene	Category 1

### Chronic aquatic toxicity

1,2,4-trimethylbenzene	Category 2
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 2
Solvent naphtha (petroleum), heavy arom.	Category 2
ethylbenzene	Category 3
mesitylene	Category 2
cumene	Category 2
Naphthalene	Category 1

% of unknown composition 8.6%

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in soil

No information available.

### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with local regulations.

### Disposal considerations

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

## 14. Transport information

### NZS5433

Proper shipping name: PAINT RELATED MATERIAL

UN number: 1263  
 Hazard Class: 3  
 Packing group: III  
 Hazchem Code: 3Y



# SAFETY DATA SHEET



Product name: ET755A A20LT SLOW THINNER

Product code: 9314042010615

Print Date: 2017-08-15

v1.0

Revision Date: 2017-08-04

NZ/en Page 8- 8

## IMDG (Sea transport)

Proper shipping name: PAINT RELATED MATERIAL

UN number: 1263  
Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: III  
Marine Pollutant: no  
EmS: F-E,S-E

## ICAO/IATA (Air transport)

Proper shipping name: PAINT RELATED MATERIAL

UN number: 1263  
Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: III

## Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

## 15. Regulatory information

### National regulatory information

HSNO Approval Code	HSR002669
HSNO Classification	
Acute oral toxicity	Category 6.1D
Acute dermal toxicity	Category 6.1E
Acute inhalation toxicity	Category 6.1D
Skin corrosion/irritation	Category 6.3A
Serious eye damage/eye irritation	Category 6.4A
Carcinogenicity	Category 6.7B
Target Organ Systemic Toxicant - Repeated exposure	Category 6.9B
Flammable liquids	Category 3.1C
Acute aquatic toxicity	Category 9.1C
Chronic aquatic toxicity	Category 9.1C

## 16. Other information

Revision Note

Version	Changes
---------	---------

1.0

Revision Date: 2017-08-04  
B12775115

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet