1. Identification of the substance/mixture and of the company/undertaking

Product name	ST200-545 A5LT 2K PU HS ACTIVATOR
Product code	ST200-545

Intended use of the substance/preparation
Hardener for professional use

Supplier	Axalta Coating Systems Australia Pty Limited
Street address	15 - 23 Melbourne Road, Riverstone NSW 2765, Australia
Telephone	
Telefax	

Emergency Information

Emergency telephone number	+(64) 9801 0034 NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248
Importer	Resene Automotive & Light Industrial
Street/Box	4 Te Apunga Place, Mt Wellington, Auckland, NZ
Nat.-Code/Postal code/City	
Telephone	+64 (09) 259 2738
Date of preparation	2015-04-10

2. Hazards identification

Classified as a Dangerous Good according to NZS 5433
Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

HSNO Classification

Flammable liquids	Category 3.1C
Skin corrosion/irritation	Category 6.3B
Respiratory sensitisation	Category 6.5A
Skin sensitisation	Category 6.5B
Acute aquatic toxicity	Category 9.1C
Chronic aquatic toxicity	Category 9.1C

Endpoints which are “”not classified“”, “”cannot classified“” and “”not applicable“” are not shown

GHS-Labelling

Hazard symbols	
Signal word	Danger
Hazard statements	Flammable liquid and vapour. Causes mild skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Precautionary statements	Avoid release to the environment. In case of inadequate ventilation wear respiratory protection. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/ vapours/ spray. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
If skin irritation or rash occurs: Get medical advice/ attention.
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep cool.

Other hazards which do not result in classification
Contains isocyanates. See information supplied by the manufacturer. Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; hexamethylene-di-isocyanate; methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

3. Composition/information on ingredients

Pure substance/mixture
Mixture

Hazardous components

CAS-No.	Chemical Name	Concentration	GHS Hazardous
28182-81-2	Hexamethylene diisocyanate, oligomers	70 - 80%	√
123-86-4	n-butyl acetate	10 - 20%	√
1330-20-7	xylene	5 - 10%	√
95-63-6	1,2,4-trimethylbenzene	1 - 3%	√
64742-95-6	solvent naphtha (petroleum), light arom. (<0,1% benzene)	1 - 3%	√
100-41-4	ethylbenzene	1 - 3%	√
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.3 - 1.0%	√
108-67-8	mesitylene	0.1 - 0.3%	√
822-06-0	hexamethylene-di-isocyanate	0.1 - 0.3%	√
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.1 - 0.3%	√

Non-regulated ingredients 0.1 - 1.0%

4. First aid measures

Eye contact
Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact
Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation
Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Ingestion
If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

Inhalation
May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion
May result in gastrointestinal distress.

Skin or eye contact
May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. Skin contact my cause skin sensitization.

Notes to physician
No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media
Universal aqueous film-forming foam, Carbon dioxide (CO2), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons
High volume water jet

Specific hazards
Flammable liquid. Vapours may form explosive mixtures with air. Remove all sources of ignition. Solvent vapours are heavier than air and may spread along floors. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

Special Protective Equipment and Fire Fighting Procedures
Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions
Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions
Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up
Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts), concentrated (d : 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts), water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to local regulations (see section 13).

7. Handling and storage

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Handling
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Safe handling advice
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

Storage
Suitable storage conditions
Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable container and packaging materials for safe storage
Always keep in containers made of the same material as the supply container.

8. Exposure controls/personal protection

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

National occupational exposure limits
Workplace Exposure Standards (WESs) 2002

Chemical Name		
Hexamethylene diisocyanate, oligomers	STEL	0.07 mg/m3
	TWA	0.02 mg/m3
n-butyl acetate	TWA	150 ppm
	STEL	200 ppm
	STEL	950 mg/m3
	TWA	713 mg/m3
xylene	TWA	50 ppm
	TWA	217 mg/m3
1,2,4-trimethylbenzene	TWA	25 ppm
	TWA	123 mg/m3
ethylbenzene	TWA	100 ppm
	STEL	125 ppm
	STEL	543 mg/m3
	TWA	434 mg/m3
mesitylene	TWA	25 ppm
	TWA	25 ppm
	TWA	123 mg/m3
	TWA	123 mg/m3
hexamethylene-di-isocyanate	STEL	0.07 mg/m3

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Chemical Name		
	TWA	0.02 mg/m3

Engineering measures
Provide adequate ventilation. Air-fed protective respiratory equipment must be worn by spray operator even when good ventilation is provided.

Protective equipment
Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection
For spraying: air-fed respirator. For operations other than spraying: in well ventilated areas, air-fed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

Eye protection
Wear protective eyewear for protection against solvent spatter.

Hand protection
The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical Name	Glove material	Glove thickness	Break through time
n-butyl acetate	Viton (R) ®	0.7 mm	10 min
	Nitrile rubber	0.33 mm	30 min
xylene	Nitrile rubber	0.33 mm	30 min
	Viton (R) ®	0.7 mm	480 min
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Viton (R) ®	0.7 mm	30 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Skin and body protection
Wear suitable protective clothing. Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures
Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

9. Physical and chemical properties

Appearance

Form : liquid Colour: clear Odor Threshold : no data available

pH	not applicable

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Freezing point	Not applicable.	
Boiling point	104 °C	
Flash point	24 °C	DIN 53213/ISO 1523
Evapouration rate	Slower than Ether	
Flammability		
Upper explosion limit	10.3 %	
Lower explosion limit	1 %	
Vapour pressure	3.3 hPa	
Solubility(ies)	partly miscible	
Vapour density	no data available	
Density	1.06 g/cm^3	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	415 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	<20 s	ISO 2431-1993 6 mm

10. Stability and reactivity

Stability
Stable

Hazardous polymerisation
Will not occur.

Conditions to avoid
Stable under recommended storage and handling conditions (see section 7).

Materials to avoid
Keep away from oxidising agents and strongly acid or alkaline materials. Amines and alcohols cause exothermic reactions. Mixture reacts slowly with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure and produces a risk of bursting.

Hazardous decomposition products
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen as well as hydrogen cyanide, amines, alcohols and water.

11. Toxicological information

Information on likely routes of exposure

Inhalation
May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion
May result in gastrointestinal distress.

Skin or eye contact
May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity
not hazardous

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Acute dermal toxicity
not hazardous

Acute inhalation toxicity
not hazardous

% of unknown composition 0 %

Skin corrosion/irritation

n-butyl acetate	Category 3
xylene	Category 2
1,2,4-trimethylbenzene	Category 2
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 3
ethylbenzene	Category 3
mesitylene	Category 3
hexamethylene-di-isocyanate	Category 1C

Serious eye damage/eye irritation
Not classified according to GHS criteria

Respiratory sensitisation

Hexamethylene diisocyanate, oligomers	Category 1
hexamethylene-di-isocyanate	Category 1

Skin sensitisation

Hexamethylene diisocyanate, oligomers	Category 1
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Category 1
hexamethylene-di-isocyanate	Category 1
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Category 1

Germ cell mutagenicity
Not classified according to GHS criteria

Carcinogenicity
Not classified according to GHS criteria

Toxicity for reproduction
Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure
Not classified according to GHS criteria

Target Organ Systemic Toxicant - Repeated exposure
Not classified according to GHS criteria

Aspiration toxicity
Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)
No information available.

Symptoms related to the physical, chemical and toxicological characteristics
Based on the properties of the isocyanate components and considering toxicological data on similar products, the following applies: This formulation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Components of the product may be absorbed into the body through the skin.

12. Ecological information

Product contains environmentally hazardous substances and product is not classified per GHS.

Ecotoxicity effects
There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

Acute aquatic toxicity

n-butyl acetate	Category 3
xylene	Category 3
1,2,4-trimethylbenzene	Category 2
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 2
ethylbenzene	Category 2
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Category 1
mesitylene	Category 2
hexamethylene-di-isocyanate	Category 3
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Category 1

Chronic aquatic toxicity

1,2,4-trimethylbenzene	Category 2
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 2
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Category 1
mesitylene	Category 2
hexamethylene-di-isocyanate	Category 3
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Category 1

% of unknown composition 0%

Persistence and degradability
No information available.

Bioaccumulation
No information available.

Mobility in soil
No information available.

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste disposal methods
Dispose of in accordance with local regulations.

Disposal considerations
A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

14. Transport information

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

NZS5433

Proper shipping name:	PAINT RELATED MATERIAL
UN number:	1263
Hazard Class:	3
Packing group:	III
Hazchem Code:	3Y

IMDG (Sea transport)

Proper shipping name:	PAINT RELATED MATERIAL
UN number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III
Marine Pollutant:	no
EmS:	F-E,S-E

ICAO/IATA (Air transport)

Proper shipping name:	PAINT RELATED MATERIAL
UN number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

National regulatory information

HSNO Approval Code	HSR002662
HSNO Classification	
Skin corrosion/irritation	Category 6.3B
Respiratory sensitisation	Category 6.5A
Skin sensitisation	Category 6.5B
Flammable liquids	Category 3.1C
Acute aquatic toxicity	Category 9.1C
Chronic aquatic toxicity	Category 9.1C

16. Other information

Revision Note

Version	Changes
2.2	3

Revision Date: 2015-04-10
B12821910

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.