



AUTO BODY EQUIPMENT

17 The Boulevard
Te Rapa, Hamilton

Ph: 07 849 3514
Fax: 07 849 3614

SAFETY DATA SHEET

DINITROL 4942

NZ Supplier details

Auto Body Equipment
17 The Boulevard, Te Rapa
Hamilton 3200 New Zealand
+64 7 849 3514
office@abe.co.nz

24hr NZ Medical Contact Details

New Zealand National
Poisons Centre
0800 764 766

HSNO Approval Number

Solvents (Flammable) Group Standard 2006

HSNO Approval Group

HSR002650

HSNO Hazards

3.1C
6.1E
6.9B

Flammable Liquids
Aspiration Hazard
Specific Target Organ
Systemic Toxicity

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: DINITROL 4942**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Anticorrosion additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Tel: +49 5281 9829 80
Fax: +49 5281 9829 860
E-mail: msds@dinol.com
- **Further information obtainable from:** Research & Development
- **1.4 Emergency telephone number:**
Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
R10-66-67: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Has a narcotizing effect.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**
- **Labelling according to EU guidelines:**
The product has been marked in accordance with EU Directives / respective national laws.
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
The R and S phrases may be omitted if packaging contains no more than 0.125 litre.
- **Risk phrases:**
10 Flammable.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**
23 Do not breathe vapour/spray.
24 Avoid contact with skin.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
51 Use only in well-ventilated areas.
60 This material and its container must be disposed of as hazardous waste.
- **2.3 Other hazards**
The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)

Trade name: DINITROL 4942

· **vPvB:** Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with additions.

· **Dangerous components:**

CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy ☒ Xn R65 R10-66-67 ☒ Flam. Liq. 3, H226; ☒ Asp. Tox. 1, H304; ☒ STOT SE 3, H336	25-<50%
aluminiumpasta ☒ F R11 R66 ☒ Flam. Sol. 1, H228	1-<5%	

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After skin contact:** If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Trade name: DINITROL 4942

(Contd. of page 2)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	Acute - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Acute - systemic effects, general population	125 mg/kg (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, general population	900 mg/m ³ (General Population)
	Long-term - systemic effects, worker	871 mg/m ³ (Worker)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber
Recommended thickness of the material: ≥ 0.12 mm

(Contd. on page 4)

Trade name: DINITROL 4942

(Contd. of page 3)

· **Penetration time of glove material**

> 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Use protective suit.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Viscous
· Colour:	Bronze coloured
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	130 °C

· **Flash point:** 37 °C (DIN 53213)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 200 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	0.6 Vol %
· Upper:	7.0 Vol %

· **Vapour pressure At 20 °C:** 3 hPa

· **Vapour pressure At 50 °C:** 13 hPa

· **Density At 20 °C:** 1.11 g/cm³ (DIN 51757)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic At 20 °C:	>2200 s (DIN 53211/4)

· **Solvent content:**

· **Organic solvents:** 33.2 %

(Contd. on page 5)

Trade name: DINITROL 4942

(Contd. of page 4)

Water:	0.2 %
Solids content:	66.6 % (DIN 53216)
· 9.2 Other information	No further relevant information available.
· VOC (EU):	33.20 %
· VOC (EU):	368.5 g/l
· VOCV:	33.20 %

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>5000 mg/kg (RABBIT)
Inhalative	LC50/4 h	> 4951 mg/l (RAT)

aluminiumpasta

Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>3000 mg/kg (RABBIT)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 6)

Trade name: DINITROL 4942

(Contd. of page 5)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1139

· **14.2 UN proper shipping name**

· **ADR** 1139 COATING SOLUTION, special provision 640E
· **IMDG, IATA** COATING SOLUTION

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids.

· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):** 30

· **EMS Number:** F-E, S-E

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **Transport category** 3

· **Tunnel restriction code** D/E

Trade name: DINITROL 4942

(Contd. of page 6)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Labelling according to EU guidelines:**
*The product has been marked in accordance with EU Directives / respective national laws.
 The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
 The R and S phrases may be omitted if packaging contains no more than 0.125 litre.*
 - **Risk phrases:**
 10 Flammable.
 66 Repeated exposure may cause skin dryness or cracking.
 67 Vapours may cause drowsiness and dizziness.
 - **Safety phrases:**
 23 Do not breathe vapour/spray.
 24 Avoid contact with skin.
 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
 51 Use only in well-ventilated areas.
 60 This material and its container must be disposed of as hazardous waste.
 - **National regulations:**
 - **Technical instructions (air):**
- | Class | Share in % |
|--------|------------|
| Wasser | 0.2 |
| NK | 33.2 |
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*
- **Relevant phrases**
 H226 Flammable liquid and vapour.
 H228 Flammable solid.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 - **Risk phrases:**
 R10 Flammable.
 R11 Highly flammable.
 R65 Harmful: may cause lung damage if swallowed.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.
 - **Department issuing MSDS:** Research & Development
 - **Contact:** Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
 - *** Data compared to the previous version altered.**