

Always use correct Personal Protective Equipment


RADIATOR BLACK

Description



Radiator Black is a fast drying product for use directly onto radiator tanks and any metal surface where a quick clean-up type paint coating is required.

Products



Product Type: Copolymer Alkyd/Hydrocarbon resin
Colour: Black
Finish: Gloss
Pot Life:

Induction Time:
Density: 0.887 kg/L
Recommended DFT: 25 microns
Theoretical Coverage:


Properties



VOC: 685 g/L
Volume Solids: 21.89%
Recoat-ability:

Dry Time @ 20°C: Touch dry: 10-15 minutes
 Hard dry: 4 hours

Substrates




Automotive components or any equipment where resistance to chemicals and prolonged exposure is not a prerequisite.

Surface Preparation



Ensure surface is washed with water and soap. Degreased with RALI Wax & Grease Remover and rough up with suitable abrasive if necessary.

Directions For Use



Mixing Ratio:
Thinning: Thin Radiator Black if necessary with GP Thinners
Application Method: Stir well. Radiator Black comes ready for use and is best sprayed with a conventional gun with a lacquer set up. Strain before application
Clean Up: GP Thinners

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Always use correct Personal Protective Equipment

Spray Equipment: Compliant / Conventional Suction and Gravity feed
Tip size: 1.6 - 2.0 mm
Air pressure: 310 - 380 kPa (45-55 psi)




Health & Safety



For detailed information refer to Safety Data Sheet (SDS). Avoid breathing vapour. Ensure adequate ventilation. Wear protective mask if working in confined spaces. Highly flammable - keep away from sparks and naked flames. If eyes become contaminated flush with water for fifteen minutes.

Transport & Storage



Sizes: 4L, 20L
Dangerous Goods: 3A
UN: 1263
Hazchem: 3(Y)E
Packing Group: III
Shipment name: PAINT Flammable
Flash point: Below 23°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.